

PRODUCT-DETAILS

OS200GB03POS200GB03P SWITCH FUSE



General Information	
Extended Product Type	OS200GB03P
Product ID	1SCA125468R1001
EAN	6417019555423
Catalog Description	OS200GB03P SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,03 (Left Side),British Standard,A2-A4,Handle and shaft included,

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311037M0206

Dimensions	
Product Net Width	192 mm

Product Net Height	146 mm
Product Net Depth /	192 mm
Length	
Product Net Weight	2.6 kg
	5.73 lb

Technical	
Rated Operational	(500 V) 160 A
Current AC-21A (I _e)	(690 V) 160 A
Rated Operational	(380 415 V) 160 A
Current AC-22A (I _e)	(500 V) 160 A (690 V) 160 A
Rated Operational Current AC-22B (I_e)	(380 415 V) 200 A
Rated Operational	(380 415 V) 160 A
Current AC-23A (I _e)	(500 V) 160 A
Rated Operational Power	(690 V) 160 A
AC-23A (P _e)	(220 240 V) 45 kW (400 V) 75 kW
	(415 V) 75 kW
	(500 V) 90 kW
	(690 V) 132 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 200 A
Conventional Thermal Current (I _{the})	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U ₁)	1000 V
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current (I _{cw})	for 1 s 5 kiloampere rms
Rated Conditional Short- Circuit Current (I _{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 14 W
Pollution Degree	3
Handle Type	Handle and shaft included
Switches Operating Mechanism	03 (Left Side)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Fuse Size	A2-A4
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	20 mm
Tightening Torque	15 22 N⋅m
Fuse Type	BS

Environmental

RoHS Status

Certificates and Declarations (Document Number)	
CCC Certificate	CCC OS200-250 2016
Declaration of Conformity - CE	1SCC311141D2703
DNV GL Certificate	1SCC311123D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC311037M0206
RoHS Information	1SCC311108D0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm
	6.7 in
Package Level 1 Depth /	220 mm
Length	8.7 in
Package Level 1 Height	150 mm
	5.9 in
Package Level 1 Gross	2.8 kg
Weight	6.1 lb
Package Level 1 EAN	6417019555423

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
ETIM 8	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Fuses

