

Visqueen ECO Temporary Protective Sheeting (TPS)

Features and benefits

- Manufactured using 100% recycled LDPE - diverts waste from landfill
- Complete range - suitable for most internal and external temporary protection applications
- Large roll formats - covers large areas fast
- Multi functional - ideal for draping, screening, covering or hanging
- Barrier properties - provides protection against showers and dust
- LDPE based - can be reused or recycled

Product description

Visqueen ECO Temporary Protective Sheeting range is manufactured from 100% recycled materials. It is supplied in rolls of 4m x 25m in three formats:

General Purpose TPS
Heavy Duty TPS
Extra Heavy Duty TPS

Approvals and standards

- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 45001:2018
- Environmental Management System ISO 14001:2015

Usage

Visqueen ECO Temporary Protective Sheeting range is a temporary covering used to protect flooring, vertical, fixtures and fittings from the effects of dust. It is also durable, and helps contain dirt and any spillages. The sheeting is easy to tailor fit as it only needs to be cut into shape.

It is suitable for screening, wrapping large objects and other site construction materials such as bricks, blocks, timber and plasterboards.

It can also be used in various other applications whilst buildings undergo refurbishment work or in new build construction projects whilst also providing protection from showers and dust.

System components

- VisqueenPro Single Sided Tape, 75mm x 25m

Find your local stockist



NEW

VISQUEEN **CLASS B FR**
VAPOUR CHECK

- Visqueen Class B FR Vapour Check is a fire resistant AVCL (air and vapour control layer)
- Surpasses all national Building Regulations and Standards for air and vapour control layers
- Fire classification B - s1, d0
- Competitive, efficient and fully tested system (including tapes) for fire resistance

NEW ANOTHER FIRE PROTECTION PRODUCT FROM VISQUEEN

To discover the Visqueen difference visit www.visqueen.com or call us on +44 (0) 333 202 6800

Visqueen ECO Temporary Protective Sheeting (TPS)

Storage and handling

Visqueen ECO Temporary Protective Sheeting should be stored horizontally, under cover in its original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Visqueen ECO Temporary Protective Sheeting can be cut with a sharp retractable safety knife or robust scissors.

Surfaces to be covered should be free from sharp protrusions. The product should be installed as soon as all surfaces or fixtures are clean.

Installation

Unroll Visqueen ECO Temporary Protective Sheeting and cut to fit the area that needs protecting.

For large covered areas it may be necessary to lap adjacent film sheets and a taped joint is recommended to ensure continuity of protection. When taping, allow an overlap of at least 50mm and secure the joint using VisqueenPro Single Sided Tape. Prior to taping ensure that the lap area is clean and free from dust and any moisture.

Usable temperature range

It is recommended that VisqueenPro Single Sided Tape should not be installed below 5°C.

Additional information

Visqueen ECO Temporary Protective Sheeting is recyclable and categorised under LDPE recycling code 4.

Visqueen is part of Berry bpi, the largest European recycler of polyethylene. This product is recyclable and should be segregated on site in accordance with site management procedures for plastic waste. We have 4 recycling sites in the UK where the plastic waste could be recycled and converted back into a second life product. Please contact us to find out more.

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

Visqueen ECO Temporary Protective Sheeting (TPS)

Property	Dimensions
General Purpose, Heavy Duty and Extra Heavy Duty - roll sizes	4m x 25m
VisqueenPro Single Sided Tape - roll size	75mm x 25m

Health and safety information

Refer to Visqueen ECO Temporary Protective Sheeting material safety datasheet (MSDS)

Visqueen ECO Temporary Protective Sheeting (TPS)

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural
Waterproofing



Gas
Protection



Damp Proof
Membrane



Tapes



Damp Proof
Course



Stormwater



Vapour
Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.