

Product datasheet

Specifications



I-Line circuit breaker, 1 Pole L1, 50A rating, 25kA, TMD trip unit adapted ComPacT NSX new generation

IL0501P251

Main

Range	I-Line
Range of product	ComPacT NSX100...250 new generation
Device short name	NSX100B
Product or component type	Circuit breaker
Device application	Distribution
Number of poles	1P
[In] rated current	50 A at 40 °C
[Ue] rated operational voltage	277 V AC 50/60 Hz conforming to EN/IEC 60947-2 250 V DC conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	25 kA Icu at 220/240 V AC 50/60 Hz conforming to EN 60947-2
Performance level	N
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Mounting location	I-Line

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
[Ics] rated service short-circuit breaking capacity	25 kA at 220/240 V AC 50/60 Hz conforming to EN/IEC 60947-2
Mechanical durability	20000 cycles
Electrical durability	20000 cycles at 277 V In 10000 cycles at 277 V In/2
Protection type	L : for overload protection (long time) I : for short-circuit protection (magnetic)
Long-time pick-up adjustment type Ir (thermal protection)	Fixed

[Ir] long-time protection pick-up adjustment range	1 In
Long-time protection delay adjustment type tr	Fixed
Instantaneous protection pick-up adjustment type li	Fixed
[Ii] instantaneous protection pick-up adjustment range	500 A
Width (W)	35 mm
Height (H)	161 mm
Depth (D)	86 mm
Net weight	0.7 kg
Colour	Grey

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-2
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Relative humidity	95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m without derating

Contractual warranty

Warranty	18 months
----------	-----------