

HARBOUR V2

10W, 20W, 28W, 34W, 40W, 58W, 70W,
80W, IP65, 2ft, 4ft, 5ft, 6ft






PRODUCT INFORMATION DOCUMENT

FEATURES

- Suitable for workshops, garages, warehouses, car parks, farm buildings, wet areas
- Flexible so will not crack when mounted on uneven surfaces
- Provides excellent light uniformity with less glare
- Less susceptible to failure due to building vibration caused by traffic or hot/cold temperature variations
- Provides ingress protection against dust and water jets
- Can easily be converted to emergency using RLEMPKDT-PSU sold as an accessory
- Plug and play microwave sensor available as an accessory (RLMW)

CONSTRUCTION

- Grey coloured polycarbonate body
- Opal polycarbonate diffuser
- Stainless steel clips



Product Code: 4000K 5000K	RHA10402FTV2-24	RHA20402FTV2-24	RHA20404FTV2-24 RHA20504FTV2-24	RHA40404FTV2-24 RHA40504FTV2-24
Comparable to:	1 x 18W T8	2 x 18W T8	1 x 36W T8	2 x 36W T8
Total Power (W):	9.8	20.2	19.9/ 19.9	38.8/ 39.3
Power Factor:	0.9	0.97	0.97	0.95
Beam Angle (Deg):	150	130	150	130
Total Light Output (lm):	1230	2510	2460/ 2450	4860/ 4720
Total Emergency Light Output (lm):	270	270	270/ 270	270/ 270
Efficacy (lm/cctW):	126	124	124/ 123	125/ 120
Lux at 1m (lux):	300	710	630/ 620	1430/ 1380
Emergency Lux at 1m (lux):	60	60	60/ 60	50/ 50
CCT (K):	4000	4000	4000/ 5000	4000/ 5000
CRI:	80	80	80	80
IP:	65	65	65	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	1.4A/5us	0.2A/5us	3A/0.1us	4.3A/0.2us
RG Value:	0	0	0	0
SDCM:	6	6	6	6
P _{ST} LM:	NA	NA	NA	NA
SVM:	NA	NA	NA	NA
Energy Class:	D	D	D	D
Rated Life to L70B50 (Hrs):	50000	50000	50000	50000
Dimensions LxWxH (mm):	650x72x70	650x117x70	1250x72x70	1250x117x70
Weight (kg):	0.68	0.92	1.14	1.62

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM
WEB: ROBUS.COM
WEB: ROBUS.COM.AU
WEB: ROBUSED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

HARBOUR V2

10W, 20W, 28W, 34W, 40W, 58W, 70W,
80W, IP65, 2ft, 4ft, 5ft, 6ft

Product Code:					
4000K	RHA28405FTV2-24	RHA58405FTV2-24	RHA80405FTV2-24	RHA34406FTV2-24	RHA70406FTV2-24
5000K	RHA28505FTV2-24	RHA58505FTV2-24		RHA34506FTV2-24	RHA70506FTV2-24
Comparable to:	1 x 58W T8	2 x 58W T8	2 x 70W T8	1 x 70W T8	2 x 70W T8
Total Power (W):	27.5/ 27.4	55.7/ 56.0	80.1	33.3/ 32.3	68.3/ 68.1
Power Factor:	0.95	0.95	0.97	0.95	0.95
Beam Angle (Deg):	150	120	130	150	130
Total Light Output (lm):	3360/ 3310	6840/ 6780	9150	3990/ 3820	8300/ 8210
Total Emergency Light Output (lm):	270/ 270	270/ 270	270	270/ 270	270/ 270
Efficacy (lm/cctW):	122/ 121	123/ 121	114	120/ 118	122/ 121
Lux at 1m (lux):	880/ 860	2070/ 2050	2780	940/ 890	2270/ 2240
Emergency Lux at 1m (lux):	50/ 50	50/ 50	50	50/ 50	50/ 50
CCT (K):	4000/ 5000	4000/ 5000	4000	4000/ 5000	4000/ 5000
CRI:	80	80	80	80	80
IP:	65	65	65	65	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	13A/12us	30A/20us	55A/3us	6A/0.7us	3.6A/0.5us
RG Value:	0	0	0	0	0
SDCM:	6	6	6	6	6
Pst LM:	NA	NA	NA	NA	NA
SVM:	NA	NA	NA	NA	NA
Energy Class:	D	D	D	D	D
Rated Life to L70B50 (Hrs):	50000	50000	50000	50000	50000
Dimensions LxWxH (mm):	1550x72x70	1550x117x70	1550x117x70	1850x72x70	1850x117x7
Weight (kg):	1.44	1.98	1.98	1.83	2.58

Separate Control Gear Information	RHA10402FTV2-24	RHA20402FTV2-24	RHA20404FTV2-24 RHA20504FTV2-24	RHA40404FTV2-24 RHA40504FTV2-24
Type of Light Source:	LED	LED	LED	LED
Full Load Efficiency (%):	93	90	91	92
P _{NET} (W):	NA	NA	NA	NA
Dimensions (mm):	144x21x22	144x21x22	144x21x22	148x34x26

Separate Control Gear Information	RHA28405FTV2-24 RHA28505FTV2-24	RHA58405FTV2-24 RHA58505FTV2-24	RHA80405FTV2-24	RHA34406FTV2-24 RHA34506FTV2-24	RHA70406FTV2-24 RHA70506FTV2-24
Type of Light Source:	LED	LED	LED	LED	LED
Full Load Efficiency (%):	92	93	93	92	94
P _{NET} (W):	NA	NA	NA	NA	NA
Dimensions (mm):	144x21x22	192x40x26	192x40x26	148x34x26	192x40x26

Product is certified to all the relevant standards.
Please contact our technical department for market specific compliances.

HARBOUR V2

10W, 20W, 28W, 34W, 40W, 58W, 70W,
80W, IP65, 2ft, 4ft, 5ft, 6ft

Cone Illuminance Diagram




Diagram for RHA58505FTV2-24 in 5000K. Other diagrams available on request

Polar Intensity Diagram





Diagram for RHA58505FTV2-24 in 5000K. Other diagrams available on request

Dimension Diagram



Accessories

- RLEMPKDT-PSU
- RLMW
- 2W 3 Hour DUAL TEST Emergency Pack
- Plug-in Microwave Sensor

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM
WEB: ROBUS.COM
WEB: ROBUS.COM.AU
WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA