

A fast install and versatile IP20 batten with press release buttons for quick opening and installation. Reliable integrated LED technology, ensuring maintenance-free installation and a long lifetime. Homogeneous illumination. Direct replacement for conventional battens in terms of light performance and length. Piano-key terminals, enabling loop-in loop-out. ENEC certified driver. 3 hour emergency lighting.


Body: sheet metal, white finish (RAL 9002).

Diffuser: polycarbonate, opal. End caps: polycarbonate, white (RAL 9002).

Weight: 4,3 kg




TE_POPPY_F_persp.jpg



TE_POPPY_M_1500.wmf

Light Distribution

Emergency



TE POPPY LED 1500 4500 840 E3e.ltd

- Light Source: LED
- Luminaire luminous flux*: 457 lm
- Luminaire efficacy*: 152 lm/W
- Colour Rendering Index min.: 80
- Chromaticity tolerance (initial MacAdam): 5
- Rated median useful life*:
L70 50000h at 25°C
- Ballast: 1x LED_Con
- Luminaire input power*: 3 W
- Dimming: Fixed output
- Total harmonic distortion (THD): 15.00 %

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.