

# T8 Luxline Plus

## F36W/T8/840

### 0001510



## PRODUCT OVERVIEW

<b>Product code</b>	0001510
<b>Product name</b>	F36W/T8/840
<b>Technology</b>	Fluorescent
<b>Watt (Rated) (W)</b>	36.00
<b>Lamp shape</b>	Tubular
<b>Type</b>	T8 Luxline Plus
<b>Cap/Base</b>	G13
<b>Lamp finish</b>	Coated
<b>Fixture rating</b>	Open
<b>General application</b>	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
<b>Certifications</b>	EUERL001
<b>ETIM Class</b>	EC000108
<b>E-number Finland</b>	4940474
<b>E-number Sweden</b>	8356604
<b>E-number Norway</b>	3815418
<b>Luminous flux (lm)</b>	3350
<b>Efficacy (lm/w)</b>	93
<b>Colour temperature (K)</b>	4000
<b>Light colour</b>	840 Cool White
<b>CRI (Ra)</b>	85
<b>Wattage (W)</b>	36.00
<b>Product Voltage (V)</b>	103
<b>Dimmable</b>	Yes
<b>Average life (Nominal) (h)</b>	20000
<b>Product EAN number</b>	5410288015101

## DATA TABLE

### General data

<b>Product code</b>	0001510
<b>Product name</b>	F36W/T8/840

## T8 Luxline Plus

F36W/T8/840

0001510

<b>Technology</b>	Fluorescent
<b>Watt (Rated) (W)</b>	36.00
<b>Lamp shape</b>	Tubular
<b>Type</b>	T8 Luxline Plus
<b>Cap/Base</b>	G13
<b>Lamp finish</b>	Coated
<b>Fixture rating</b>	Open
<b>General application</b>	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
<b>Certifications</b>	EUERL001
<b>ETIM Class</b>	EC000108
<b>E-number Finland</b>	4940474
<b>E-number Sweden</b>	8356604
<b>E-number Norway</b>	3815418

## Optical data

<b>Luminous flux (lm)</b>	3350
<b>Luminous flux (Rated) (lm)</b>	3350
<b>Efficacy (lm/w)</b>	93
<b>Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.</b>	93
<b>FieldId_390</b>	93.00
<b>Ambient temperature for maximum luminous flux (°C)</b>	25
<b>Colour temperature (K)</b>	4000
<b>Correlated colour temperature range (K)</b>	4000
<b>Light colour</b>	840 Cool White
<b>CRI (Ra)</b>	85
<b>Adjustable chromaticity</b>	N
<b>Rated lumen maint. factor (%) at 2000 h 50Hz</b>	0.96
<b>Rated lumen maint. factor (%) at 4000 h 50Hz</b>	0.94
<b>Rated lumen maint. factor (%) at 6000 h 50Hz</b>	0.92
<b>Rated lumen maint. factor (%) at 8000 h 50Hz</b>	0.91
<b>Rated lumen maint. factor (%) at 12000 h 50Hz</b>	0.90
<b>Rated lumen maint. factor (%) at 16000 h 50Hz</b>	0.89
<b>Rated lumen maint. factor (%) at 20000 h 50Hz</b>	0.87

## T8 Luxline Plus

F36W/T8/840

0001510

## Electrical data

<b>Wattage (W)</b>	36.00
<b>Watt (Rated) - High frequency (W)</b>	32.00
<b>Current (A)</b>	0.430
<b>Mains voltage (V)</b>	220-240V~
<b>Product Voltage (V)</b>	103
<b>Control gear required</b>	Yes
<b>Transformer required</b>	No
<b>Dimmable</b>	Yes
<b>Drive current (mA)</b>	430
<b>Lamp Energy Label (class)</b>	A
<b>Energy efficiency level</b>	A
<b>kWh per 1000 hours burning time</b>	43

## Lifetime data

<b>Average life (Nominal) (h)</b>	20000
<b>Average life (Rated) (h)</b>	20000
<b>Rated survival factor (%) at 2000 h 50Hz</b>	0.99
<b>Rated survival factor (%) at 4000 h 50Hz</b>	0.98
<b>Rated survival factor (%) at 6000 h 50Hz</b>	0.96
<b>Rated survival factor (%) at 8000 h 50Hz</b>	0.94
<b>Rated survival factor (%) at 12000 h 50Hz</b>	0.92
<b>Rated survival factor (%) at 16000 h 50Hz</b>	0.80
<b>Rated survival factor (%) at 20000 h 50Hz</b>	0.50

## Physical data

<b>Nominal Product Length (mm)</b>	1200.0
<b>Nominal Product Diameter (mm)</b>	26
<b>Max. Length base to base (mm) - A</b>	1199.4
<b>Length base to pin Min-Max (mm) - B</b>	1204.1-1206.5
<b>Max. Lamp Length (mm) - C/L</b>	1213.6
<b>Max. Lamp Diameter (mm) - D</b>	28.0
<b>Weight (kg)</b>	0.159

## Packaging

<b>Single packaging type</b>	Carton
<b>Product EAN number</b>	5410288015101
<b>Packaging single length (cm)</b>	2.8
<b>Packaging single width (cm)</b>	2.9
<b>Packaging single height (cm)</b>	121.4

# T8 Luxline Plus

## F36W/T8/840


### 0001510

<b>DUN14 (outer)</b>	15410288015108
<b>Units per outer package</b>	25
<b>Packaging outer length (cm)</b>	124.0
<b>Packaging outer width (cm)</b>	15.5
<b>Packaging outer height (cm)</b>	15.0


#### Safety data

<b>Lamp mercury content (mg)</b>	2.80
<b>Breakage cleaning instructions</b>	Applicable
<b>Recommendation for disposal at end of life</b>	Applicable
<b>Special purpose lamp</b>	No
<b>Intended purpose</b>	General lighting
<b>Suitable for household illumination</b>	Yes

#### PHOTOMETRY



#### TECHNICAL DRAWINGS



T8 Luxline Plus

F36W/T8/840

**0001510**

