



SBC Stamped Beam Clamp, Top Mount

Features

- Allows structural attachment to metal beams, bar joist, channel, or angle iron in top mount position only unless used on a parallel flange
- Lightweight, one-piece stamped body provides superior strength and eliminates deficiencies associated with castings
- Spins onto threaded rod and allows for easy adjustment
- Conforms with Federal Specification WW-H-171 (Type 23), Manufacturers Standardization Society ANSI®/MSS-SP-58 (Type 19)



Material: Steel
Finish: Pregalvanized


Part Number	Article Number	Rod Size	Flange Thickness	A	B	C	Screw Diameter	Torque	Static Load
SBCM10	386821	M10	19 mm Max	23.5 mm	21.6 mm	40.1 mm	9.5 mm	6.78 N-m	2,200 N

Set screw must be tightened and torqued onto the sloped side of the I-beam, channel, or angle iron flange.

EBC Beam Clamp

Features

- Easy installation to beam flanges



Material: Spring Steel
Finish: CADDY ARMOUR

Part Number	Article Number	Rod Size	Hole Size	Flange Thickness	Torque	Static Load	Standard Packaging Quantity
EBC	170380	M6	10.5 mm	16 mm Max	3 N-m	450 N	100 pc
EBCSP25	172430	M6	10.5 mm	16 mm Max	3 N-m	450 N	10 x 25 pc

Setscrew must be tightened and torqued onto the sloped side of the I-beam.