


Hammer-On Flange Clip, Bottom Mount with Stud

Features

- Can be used to support boxes, fixtures or other applications from beam flanges
- Captive threaded stud minimizes the need for additional hardware
- Assorted attachment points provided to reduce inventory
- Requires only a hammer to install




Part Number	Article Number	Flange Thickness	Rod Size	Screw Diameter	Screw Length	Static Load 1	Static Load 2	Static Load 3	Standard Packaging Quantity
Material: Stainless Steel 301 [EN 1.4310]									
EM24SS1	179750	3 – 8 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
EM58SMS1	179760	8 – 14 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
EM912SS1	179770	14 – 20 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
Material: Steel, Spring Steel — Finish: CADDY ARMOUR									
EM24SM	170530	3 – 8 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
EM24SM16	160440	3 – 8 mm	M6	M6	16 mm	450 N	330 N	110 N	100 pc
EM24SM16SP10	172220	3 – 8 mm	M6	M6	16 mm	450 N	330 N	110 N	10 x 10 pc
EM58SM	172060	8 – 14 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
EM58SM16	160450	8 – 14 mm	M6	M6	16 mm	450 N	330 N	110 N	100 pc
EM58SM16SP10	172230	8 – 14 mm	M6	M6	16 mm	450 N	330 N	110 N	10 x 10 pc
EM912SM	171850	14 – 20 mm	M6	M6	11 mm	450 N	330 N	110 N	100 pc
EM912SM16	160460	14 – 20 mm	M6	M6	16 mm	450 N	330 N	110 N	100 pc
EM912SM16SP10	172240	14 – 20 mm	M6	M6	16 mm	450 N	330 N	110 N	10 x 10 pc

Hammer-On Flange Clip, Side Mount

Features

- Provides an attachment for wire, S-hooks, chain, CADDY SPEED LINK or other assemblies to flanges and profiles
- Fits most beams
- Installs with just a hammer



Part Number	Article Number	Flange Thickness	Hole Size	Static Load	Certifications	Standard Packaging Quantity
Material: Spring Steel — Finish: CADDY ARMOUR						
2H4	170010	2 – 3 mm	7.1 mm	700 N	cULus	100 pc
4H24	170020	3 – 8 mm	7.1 mm	900 N	cULus	100 pc
4H24SP25	172320	3 – 8 mm	7.1 mm	900 N		10 x 25 pc
4H58	170030	8 – 14 mm	7.1 mm	900 N	cULus	100 pc
4H58SP25	172350	8 – 14 mm	7.1 mm	900 N		10 x 25 pc
4H912	170040	14 – 20 mm	7.1 mm	900 N	cULus	100 pc
4H912SP25	172380	14 – 20 mm	7.1 mm	900 N		10 x 25 pc
Material: Stainless Steel 301 [EN 1.4310]						
4H24S1	179610	3 – 8 mm	7.1 mm	650 N		100 pc
4H58S1	179620	8 – 14 mm	7.1 mm	650 N		100 pc
4H912S1	179630	14 – 20 mm	7.1 mm	650 N		100 pc

