


EM-M Conduit/Pipe to Flange Clip

Features

- Supports conduit/pipe or cable from beam flanges
- Snap close clip pivots a full 360°
- Requires only a hammer to install



Part Number	Article Number	Outer Diameter	Flange Thickness	Static Load
Material: Spring Steel — Finish: CADDY ARMOUR				
16EM24	171740	30 – 35 mm	3 – 8 mm	330 N
16EM58	171490	30 – 35 mm	8 – 14 mm	330 N
16EM912	173570	30 – 35 mm	14 – 20 mm	330 N
20EM24	171800	35 – 42 mm	3 – 8 mm	330 N
20EM58	171950	35 – 42 mm	8 – 14 mm	330 N
20EM912	173580	35 – 42 mm	14 – 20 mm	330 N
24EM24	171960	42 – 50 mm	3 – 8 mm	330 N
24EM58	171970	42 – 50 mm	8 – 14 mm	330 N
24EM912	173590	42 – 50 mm	14 – 20 mm	330 N
32EM24	173600	50 – 60 mm	3 – 8 mm	330 N
32EM58	173610	50 – 60 mm	8 – 14 mm	330 N
32EM912	173620	50 – 60 mm	14 – 20 mm	330 N
6EM24	173550	14 – 18 mm	3 – 8 mm	330 N
6EM58	171750	14 – 18 mm	8 – 14 mm	330 N
6EM912	173560	14 – 18 mm	14 – 20 mm	330 N
812EM24	160120	18 – 30 mm	3 – 8 mm	330 N
812EM58	160130	18 – 30 mm	8 – 14 mm	330 N
812EM912	160140	18 – 30 mm	14 – 20 mm	330 N
Material: Stainless Steel 301 [EN 1.4310]				
12EM24S1	179810	22 – 30 mm	3 – 8 mm	200 N
12EM58S1	179820	22 – 30 mm	8 – 14 mm	200 N
12EM912S1	179830	22 – 30 mm	14 – 20 mm	200 N
8EM24S1	179780	18 – 22 mm	3 – 8 mm	200 N
8EM58S1	179790	18 – 22 mm	8 – 14 mm	200 N
8EM912S1	179800	18 – 22 mm	14 – 20 mm	200 N