


Lamp Options

- 8W T5 fluorescent, 3500°K - G5 cap

Materials

- Body and gear cover - steel, powder coated in RAL9016 white finish
- Legend panel - clear acrylic with rear screen printing
- Downlight panel - opal polycarbonate
- Batteries (self-contained versions) - NiCd

Dimensions



Catalogue Numbers

System Mode	Cat No	Weight (kg)
Non Maintained 3Hr	SE83ICEL	3.5
Non Maintained 3Hr Self-test	SE83IS	3.5
Non Maintained 3Hr EasiCheck	SE83EC	3.5
Non Maintained 3Hr EasiCheck 2	SE83EC2	3.5
Maintained 3Hr	SE83MICEL	3.6
Maintained 3Hr Self-test	SE83MIS	3.6
Maintained 3Hr EasiCheck	SE83MEC	3.6
Maintained 3Hr EasiCheck 2	SE83MEC2	3.6
230V Ceaguard Slave	SE8230CG	2.1
230V AC Mains Slave	SE8230	2.1
230V AC Mains Slave EasiCheck	SE8230EC	2.1
50V AC/DC Central System Slave	SE850	2.1
110V AC/DC Central System Slave	SE8110	2.1

Legend Panel	Pictogram	Cat No	Weight (kg)
Down arrow		SEAD	0.10
Left arrow		SEAL	0.10
Right arrow		SEAR	0.10

Options

- Maintained and non-maintained, 3 hour duration
- EasiCheck addressable testing. System detailed on page 304
- Central system slave versions
- Choice of legend panels

Specification

Self contained - To specify state: BSI Kitemarked, back-lit, large format self contained emergency sign, with large downlight panel and 41m viewing distance legends, as JSB Exit SE range, part no. _____

Slave - To specify state: Central system slave, back-lit, large format emergency sign, with large downlight panel and 41m viewing distance legends, as JSB Exit SE range, part no. _____

Maximum Viewing Distance

