

SWD Industrial Finned Tubular Heaters

- Ideal for damp and corrosive environments
- Suitable for 'hose-down' washing
- Designed for long life in the most demanding conditions

Features

- Welded stainless steel construction
- Built-in adjustable thermostat (SWD-A models only)
- Brackets for wall or floor mounting supplied as standard
- Waterproof glass fibre terminal box IP66 rated
- M20 cable gland supplied as standard
- Optional zinc plated wire guards available (recommended when personnel have access to the heater)



SWD Industrial Finned Tubular Heater ideal for damp and corrosive environments

Heater Range

Model	kW	Volts	Built-in Thermostat
SWD-A-500	0.5	230V	Yes
SWD-A-1000	1.0	230V	Yes
SWD-A-1500	1.5	230V	Yes
SWD-A-2000	2.0	230V	Yes
SWD-A-3000	3.0	230V	Yes
SWD-U-500	0.5	230V	No
SWD-U-1000	1.0	230V or 400V/3	No
SWD-U-1500	1.5	230V or 400V/3	No
SWD-U-2000	2.0	230V or 400V/3	No
SWD-U-3000	3.0	230V or 400V/3	No
SWD-U-4000	4.0	230V or 400V/3	No
SWD-U-500-1	0.5	110V	No
SWD-U-1000-1	1.0	110V	No
SWD-U-1500-1	1.5	110V	No

Heater Technical Data

kW	Dimensions (mm)			Weight (kg)	Optional Guard
	L	W	H		
0.5	440	130	170	3.0	SWG-1
1.0	640	130	170	4.8	SWG-2
1.5	840	130	170	6.2	SWG-3
2.0	1040	130	170	7.7	SWG-3
3.0	1440	130	170	10.9	SWG-4
4.0	1840	130	170	13.7	SWG-5



SWD-A with externally adjustable thermostat



SWD-U standard format