



Churchfields Industrial Estate, Hastings

East Sussex, TN38 9PU

Customer Services: 01424 856600 Technical Hotline: 01424 856688

Fax: 01424 856611

Email: sales@marshall-tufflex.com www.marshall-tufflex.com

MT Supertube Product Data Sheet

Product Range	22003 & 22503
Description	LSOH 3-layer heavy gauge Conduit
Key Features	LSOH Conduit Excellent Screening Performance Suitable for Rail, Marine and Tunnel apps. Supplied in continuous lengths up 100m Suitable of in-screed apps. EMC/EMI Boxes and Fittings Withstands temp. from -45°C to +120°C
Dimensions	20mm O.D. (22003) & 25mm O.D. (22503)
Material(s)	LSOH polyethylene with Aluminium core
Compliance / Standard(s)	CE Marked BS 7671:2008+A3:2015 EC Directive 200/95/EC, EC Directive 2004/108/EC BS EN 61386-1:2008 BS EN 61386-21:2010 DIN VDE 0281-13:2003-02 Section 4.3.5 DIN EN50289-1-6:2002-12 Section 6 IEC 60227-1:2003-04 Section 2.3.5
Packaging	Recyclable



Carbon assessment

The Carbon Trust was set up by Government in 2001 as an independent company. Their mission is to accelerate the move to a low carbon economy by working with organisations to reduce carbon emissions and develop commercial low carbon technologies. Marshall-Tufflex was assessed by the Carbon Trust in 2007and received an excellent report.

Sustainability

MT Supertube manufactured from a layers or Polyethylene and Aluminium. - non-recyclable

Quality Management Systems	Environmental Management Systems
Marshall-Tufflex is totally committed to quality and customer satisfaction and the Company is recognised by the British Standards Institution as a firm of Assessed Capability to BS EN ISO 9001:2008.	Marshall-Tufflex is totally committed to achieving high environmental standards. The Company is recognised by the BSI as a firm of Assessed Capability to BS EN ISO 14001:2004 (Environment) and BS EN ISO 50001:2011 (Energy).

DOC00287 Issue 6







A MEMBER OF THE MARSHALL-TUFFLEX GROUP OF COMPANIES