


Ducting & Accessories

Double Air Brick




Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
438604	204 x 60 (White)	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4
438607	204 x 60 (Terracotta)	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4
438605	204 x 60 (Brown)	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4
438606	204 x 60 (Beige)	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4

Double Air Brick Adaptor



		External Dimensions			Resistance (Pa) at flow rate							
Stock Ref	Duct Size	A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
438608	204 x 60	135	220	85	-	-	-	-	-	-	-	-

Air Grille Adaptor



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
436609	110 x 54	65	210	85	0.2	1.2	2.5	4.7	7.8	11	14	18

Flexible Ducting



g

Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
5109662	204 x 60	-	-	-	0.2	0.6	1.5	2.6	4.1	6.0	8.2	11.5
Stock Ref	Duct Size	A	B	C	60 l/s			120 l/s			180 l/s	
449366	220 x 90	-	-	-	N/A			N/A			N/A	

Louvred Grille with Flyscreen fitting



with Flyscreen fitting		External Dimensions			Resistance (Pa) at flow rate							
Stock Ref	Duct Size	A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
400743	110 x 54	140	140	50	5.7	14.5	37	75	120	-	-	-

Round (M) 100mm to Rectangular (F/M) Adaptor



50mm to Rectangular (F/M) Adaptor

Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
441654	M to F 204 x 60	140	210	215	1.0	1.96	3.2	4.9	6.7	8.7	11.2	14.5
400740	M to M 110 x 54	100	115	180	1.2	4.2	8.3	19.8	29.9	42	60	86

Round (F) 125mm to Rectangular (F) Adaptor



mm to Rectangular (F) Adaptor												
Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
370127	F to F 204 x 60	140	210	213	<1	<1	1.5	2.8	4.5	6.7	9	11.5

Round (F) 150mm to Rectangular (F) Adaptor



mm to Rectangular (F) Adaptor							
Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate		
		A	B	C	60 l/s	120 l/s	180 l/s
403031	F to F 220 x 90	160	225	203	N/A	N/A	N/A

Short Round (M) 100mm to 110 x 54 (F) Adaptor



A) 100mm to 110 x 54 (F) Adaptor												
Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
455035	M to F 110 x 54	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88