

COMMERCIAL

ATMOS LED PANEL



ATMOS LED PANEL, 600X600MM, WHITE

- Suitable for use in offices, shops, reception areas, restaurants, hotels, schools, hospitals
- UGR ≤19 for small offices to comply with EN12464
- A high quality PP thermoplastic diffuser ensures that light transmission is maximised into the lit space and provides a TP_a rating to comply with fire regulations
- Wide operating ambient temperature range of -20°C to +40°C
- Emergency pack provides high lumen output to comply with emergency lighting regulations using minimum number of fittings and utilises LiFePO₄ battery technology for long life
- Full range of mounting accessories available for all installation types
- Suitable for switching by external PIR, Microwave or Photocell


ACCESSORIES

R3EMPK4-PSU	3 Hour Emergency Pack with LifePO ₄ Battery
R6060SMKFB-01	Flat packed surface mount box 600x600mm
RAMSUS-4W	4 wire suspension kit 600x600mm
RAMSST	Safety bracket and 2m strap 600x600mm
RAM40FFDVR	Flicker free driver
HED2040-D	1-10V, DALI and Push dim driver available
RAMRC	Plaster board recessed clips kit
RPLBRK-01	Adjustable surface mount bracket

CONVERSIONS AVAILABLE




DIMENSIONS(mm)	Width	Length	Depth
RAM40306060-01	595	595	10
RAM40406060-01	595	595	10
RAM40506060-01	595	595	10





	Warm White	Neutral White	Cool White
Standard	RAM40306060-01	RAM40406060-01	RAM40506060-01
C/w Push Connector	RAM40306060X-01	RAM40406060X-01	N/A
	600 x 600mm	600 x 600mm	600 x 600mm
Comparable to:	4x18W Fluorescent	4x18W Fluorescent	4x18W Fluorescent
Total Power (W):	38.1	38.3	37.7
Total Light Output (lm):	3,390	3,810	3,800
Efficacy (lm/cctW):	89	99	101
Lifetime (hrs):	50,000	50,000	50,000
Beam Angle (deg):	110	110	110
Lux at 1m (lux):	1,170	1,310	1,310
CCT (K):	3000	4000	5000
CRI (Ra):	80	80	80
Power Factor (PF):	0.97	0.97	0.97
Impact Rating (IK):	06	06	06
Box Qty:	1/4	1/4	1/4
Weight (kg):	2.0	2.0	2.0



SEAI approved