




360° PIR

- Suitable for use with ROBUS; CAESAR LED battens, HARBOUR, SULTAN and VULCAN LED corrosion proof fittings and ALEXANDER LED batten
- Polycarbonate housing
- Remote control option available
- Step dimming function only available for products with dimmable driver option



R360PIR-01	
Maximum Switching Capacity (W):	450
Warranty (yrs):	3
Detection Angle (deg):	360
IP:	65
Mounting Height Range (m):	2.5 – 7 max
Impact Rating (IK):	10
Operating Temperature (°C):	-10 ≤ Ta ≤ +40
Operating Voltage (Vac):	220-240
Default Sensitivity [%]:	100
Default Hold Time (min):	5
Default Lux Switching Level:	Full Daylight
Default Standby Level Before Off [%]:	20
Default Standby Time Before Off (min):	60
Box Qty:	1
Weight (kg):	0.1

PIR REMOTE CONTROL

- Maximum remote operation of 7m
- PIR Remote control accesses the below extended sensor functionality

R360RC-01	
Detection Sensitivity [%]:	100/75/50/20
Hold Time:	10sec/1min/5min/15min/30min/60min
Standby Level Before Off [%]:	0/10/20/30
Standby Time Before Off:	1min/30min/60min/24Hrs
Lux Switching Level (lx):	50 lx
Remote Range (m):	10m Max
Memory Function:	Enter single program to memory button, to allow for rapid programming of additional sensors



DIMENSIONS(mm)	Width	Length	Depth
R360PIR-01	36	149	28
R360RC-01	52	85	10

