

Trac™

GU10 Single Circuit Track

make smart with



See pg.256-258 for compatibility table

Cast aluminium track spotlight with slimline single circuit track adaptor

Compatible with industry standard Global single circuit track

Adjustable rotation 350° and 180° tilt

For use with GU10 lamps - lamp not included

Use with EN-TK2

Smart

Lamp options
See pg.27



Use with EN-TK2

Standard

Lamp options
See pg.113



Use with EN-TK1

High Output

Lamp options
See pg.114



See luminaire lamp compatibility on pg.259



Short Form



Long Form

Cat. No. Input

Long Form

EN-TK1* 240V

Short Form

EN-TK2* 240V

Accessories

#GB2100-† Global 1m Single Circuit Track

#GB21-† Global Straight Connector Single Circuit Track

#GB11-† Global Live End Connector Single Circuit Track

#GB41-† Global Dead End Connector Single Circuit Track

†Add suffix **2** for Black or **3** for White option

*Add suffix **W** or **BLK** for White or Black option

Lamp not included



3 Year Warranty

Black or White finish options

make smart with




works with

.light




Smart
Tuneable GU10
See pg.27


.control




Dimmable
Standard GU10
PLUS
Triac Inline Dimmer
See pg.41



OR
Smart Rotary Dimmer
See pg.35



Non-Dimmable
Standard GU10
PLUS
On/Off Relay
See pg.47



EN-TK1

(L) 130mm Length
(OD) 60mm Overall (Ø)
(SL) 40mm Stem Length

EN-TK2

(L) 100mm Length
(OD) 60mm Overall (Ø)
(SL) 40mm Stem Length