

Product Code: MD018BK-WM

Description: 13A/10AX Double Pole Switch Module



General Information

|                         |                                                                                                                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions              | 25mm (W) x 53mm (H) x 20mm (D)                                                                                                                                                                     |
| Aperture Dimensions     | 16mm (W) x 31.5mm (H)                                                                                                                                                                              |
| Finish                  | Black                                                                                                                                                                                              |
| Materials               | Rocker Switch: Urea<br>Rear Housing: Nylon<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass |
| Maximum Voltage         | 250V 50Hz                                                                                                                                                                                          |
| Load Rating             | 13A/10AX (Suitable For Inductive Loads)                                                                                                                                                            |
| Terminal Size           | 3.5mmø                                                                                                                                                                                             |
| Terminal Torque         | 0.4Nm                                                                                                                                                                                              |
| Terminal Capacity       | 4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>                                                                                                                                                   |
| Product Markings        | Washing Machine                                                                                                                                                                                    |
| Back Box Depth          | Dependent On Plate Used                                                                                                                                                                            |
| Operational Temperature | -5°C to +40°C                                                                                                                                                                                      |
| Warranty                | 10 Years                                                                                                                                                                                           |
| Standards               | BS EN 60669-1:1999 +A1:2002 +A2:2008                                                                                                                                                               |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.