

LED Ultra Slim Link Light Fittings

The KingShield range of LED Ultra Slim fittings are supplied complete with a Cool white (4,000K) LED lamp, 2 metre power/link lead, prismatic diffuser and mounting brackets (clips).

Up to 30 of the same wattage fittings can be interlinked by butt and/or lead connections.



- Ideal for unobtrusive display applications, pelmets, under shelves, bookcases and cabinets
- Cool white (4,000K)
- 120° beam angle
- Ultra slim design
- Individually switched
- Flicker free quick start
- 3 year warranty

Technical Data

Voltage	230V AC - 50Hz
Conforms to	EN 60598-1:2008+A11:09 EN 60598-2-1:1989 EN 61347-1:2008+A1:11 EN 61347-2-13:2006



Part No	Description	Dimensions
SLLLED3	LED 3W Ultra Slim Link Light 86.9 lm/W LED's array 18 piece	L267 x W22 x H44mm
SLLLED4	LED 4W Ultra Slim Link Light 84.6 lm/W LED's array 24 piece	L343 x W22 x H44mm
SLLLED7	LED 7W Ultra Slim Link Light 85.9 lm/W LED's array 40 piece	L571 x W22 x H44mm
SLLLED14	LED 14W Ultra Slim Link Light 84.4 lm/W LED's array 62 piece	L604 x W22 x H44mm
SLLLED18	LED 18W Ultra Slim Link Light 84.8 lm/W LED's array 84 piece	L904 x W22 x H44mm
SLLLED22	LED 22W Ultra Slim Link Light 85.6 lm/W LED's array 102 piece	L1204 x W22 x H44mm

