

OUTDOOR MICRO ACTIVATE LED FLOODS



30W White



50W Dark Grey

MICRO ACTIVATE LED Floodlight

- Suitable for use in decking areas, drives, pathways, sign illumination, wall washing, atriums, patios, car parks, garages, industrial units
- Energy efficient replacement for linear halogen and metal halide fittings
- Pre-wired with 1m of rubber flex
- C/w 180° adjustable bracket
- High impact resistant (IK09)
- Die-cast aluminium housing with durable high quality paint finish
- Suitable for use with PIRs. LED flood lights have no re-striking time associated with metal halide and SON fittings and can be switched on and off in quick succession
- PIR version has sensor with adjustable time 10sec to 20min and detection range of 1m to 8m
- IP65 rating for both standard and PIR versions



SPIKE polycarbonate

- For use with 10W, 20W and 30W MICRO ACTIVATE LED floods

R210MMSPIKE

Height (mm): 210



LED floodlight signage arm, for use with OLYMPIC & MICRO ACTIVATE floods

- 600mm arm allows projected illumination for signage and other display purposes
- For use with 10W / 20W/ 30W OLYMPIC & MICRO ACTIVATE floods

R10FSA-01	White
R10FSA-04	Black
R10FSA-24	Grey
Proj (mm):	600



30W PIR Dark Grey



30W PIR white

Neutral White

	30W	50W
Standard White	RMA03040-01	RMA05040-01
Standard Grey	RMA03040-25	RMA05040-25
PIR White	RMA03040DG-01	
PIR Grey	RMA03040DG-25	
Comparable to:	50W metal halide 200W halogen	80W Metal Halide 350W Halogen
Total Power (W):	29.4	48.6
Total Light Output (lm):	2,470	4,070
Efficacy (lm/cctW):	84	84
Lifetime (hrs):	35,000	35,000
Lux at 1m (lux):	750	1,250
Beam Angle (deg):	120	120
CCT (K):	4,000	4,000
CRI:	80	80
IP:	65	65
Power Factor:	0.95	0.95
Width (mm):	240	299
Height (mm):	165/269	210
Depth (mm):	29.5	210
Box Qty:	1	1
Weight (kg):	1.40	2.36

