



See pages 66 – 68
for Product Information



		TPS101	TPS201	TPS203	TPS204	TPS401
Type		Single Gang Socket	Twin Gang Socket	Combined 13A Socket & DP Switch	Combined RCD Socket	Multi Box with 4 Gang 13A Socket Strip
Weatherproof Rating		IP55	IP55	IP55	IP55	IP55
Operating Voltage	230V 13 Amp (3kW)	•	•	•	•	•
Rocker Switch Poles				2		
Rocker Switch Rating	230V 13 Amp (3kW)			•		
Operating Temperature	0°C to 40°C	•	•	•	•	•
RCD Trip Speed	BS7288 – 40ms				•	
Continues to Protect with	Lost Neutral & Pulsating DC Earth Fault				•	
Cable Capacity	3x 2.5mm ²	•	•	•	•	5x 2.5mm ²
EC Directives	Conforms to Latest Directives	•	•	•	•	
Dimensions (mm)	Height	70	70	70	70	265
	Width	70	147	147	147	355
	Depth	54	54	54	54	120



See page 68
for Product Information



		TPSL01	TPSL02	TPSL03	TPSL04
Type		2 Way	2 Gang 2 Way	Bell	DP Switch
Weatherproof Rating		IP55	IP55	IP55	IP55
Operating Voltage	230V 13 Amp (3kW)	•	•	•	•
Rocker Switch Poles		1	1	1	2
Rocker Switch Rating	230V 13 Amp (3kW)	10 AX	10 AX	10 AX	20 AX
Operating Temperature	0°C to 40°C	•	•	•	•
Cable Capacity	3x 2.5mm ²	•	•	•	•
EC Directives	Conforms to Latest Directives	•	•	•	•
Dimensions (mm)	Height	70	70	70	70
	Width	70	70	70	70
	Depth	55	55	55	55



See pages 70 – 71
for Product Information



		IS3N-20	IS4N-20	IS3N-32	IS4N-32	IS4N-40	IS4N-63	IS4N-100
Weatherproof Rating	IP65	•	•	•	•	•	•	•
Operating Voltage	230V AC	•	•	•	•	•	•	•
Rotary Switch Poles	3 or 4	3	4	3	4	4	4	4
Rotary Switch Rating	Amps	20	20	32	32	40	63	100
Operating Temperature	0°C to 40°C	•	•	•	•	•	•	•
On Load Switch Disconnectors		•	•	•	•	•	•	•
EC Directives	Conforms to Latest Directives	•	•	•	•	•	•	•
Dimensions (mm)	Height	100	100	125	125	175	175	240
	Width	80	80	98	98	111	111	155
	Depth	100	100	120	120	135	135	160



See pages 72 – 75
for Product Information



		EACP1	EACP1PR	EACP4	EACP4PR	EARB1	EAPC1	EADF1	EAPB1	EAAB1
Switch Type	Single or Double Gang	Double	Double	Double	Double	Single	Surface Mount	Single	Single	Single
Operating Voltage	230V AC	•	•	•	•	•	•	•	•	•
Unit Finish	White Plastic	•	•	•	•	•	•	•	•	•
Zone Detection		Single	Single	Four	Four					
Alarm	65dB Continuous	•	•	•	•	•		78dB Intermittent		
System 'Live' Status		•	•	•	•	•				
Auto Fault Detection		•	•	•	•	•				
Power Reserve	Typically 4 Days in Standby		•		1 Day					
	2 Hours in Continuous Alarm		•		30 Minutes					
Cable Capacity	3x 1.5mm ²	•	•	•	•	•	•	•	•	•
	7/0.2	•	•	•	•	•	•	•	•	•
EC Directives	Conforms to Latest Directives	•	•	•	•	•	•	•	•	•
Dimensions (mm)	Height	85	85	85	85	85	82Ø	85	80	85
	Width	145	145	145	145	85		85	72	85
	Depth	33	33	33	33	12	20	24	65	12
Min. Box Depth	25mm	•	•	•	•	•		•	•	•



See pages 72 – 75
for Product Information



		EASSCP1	EASSCP1PR	EASSCP4	EASSCP4PR	EASSRB1	EAPC1	EASSDF1
Switch Type	Single or Double Gang	Double	Double	Double	Double	Single	Surface Mount	Single
Operating Voltage	230V AC	•	•	•	•	•		•
Unit Finish	Stainless Steel	•	•	•	•	•		
Zone Detection		Single	Single	Four	Four			
Alarm	65dB Continuous	•	•	•	•	•		78dB Intermittent
System 'Live' Status		•	•	•	•	•		
Auto Fault Detection		•	•	•	•	•		
Power Reserve	Typically 4 Days in Standby		•		1 Day			
	2 Hours in Continuous Alarm		•		30 Minutes			
Cable Capacity	3x 1.5mm ²	•	•	•	•	•	•	•
	7/0.2	•	•	•	•	•	•	•
EC Directives	Conforms to Latest Directives	•	•	•	•	•	•	•
Dimensions (mm)	Height	85	85	85	85	85	82Ø	85
	Width	145	145	145	145	85		85
	Depth	33	33	33	33	12	20	24
Min. Box Depth	25mm	•	•	•	•	•		•



See page 76
for Product Information



		SPA3G	SPS4G	SPS6G	SPS8G	SPS10G
Number of Ways		3	4	6	8	10
Operating Voltage	230V AC	•	•	•	•	•
Surge Rating (max.)	4500A	•	•	•	•	•
Mains Protection Mode	L-N, N-E, L-E	•	•	•	•	•
Maximum Current	13A (3kW)	•	•	•	•	•
Operating Temp Range	0°C to 40°C	•	•	•	•	•
Factory Fitted Fuse	BS1362 13A	•	•	•	•	•
Power Consumption	0.2W	•	•	•	•	•
EC Directives	Conforms to Latest Directives	•	•	•	•	•
Dimensions (mm)	Height	65	60	60	150	125
	Width	50	270	380	365	380
	Depth	80	25	25	30	25