

TKE/B 50



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Brass nickel-plated
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP69, IP68 (5 bar 30 min)
Surface	Nickel-plated
Thread type	M
Ø Connection thread D	50
Lead	1,5
Length screw-in thread L	9 mm
Key width SW	55 mm
Total length TL	51 mm - 62 mm
Type of cable anchorage	A
Install. torques fitting	30 N/m
Install. torques cap nut	30 N/m
Impact category	6
Order no. nickel-plated	10106236
Type	TKE/B 50
Packing unit	1
ETIM-Classification	EC000441

Description:

IP 68 Brass cable gland. EMSKV 50/ MFD 4 x 11 mm Tails and 1 x 6 mm Earth. Kit contains insert, locknut and blanking insert.

13.10.2020

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk