


Ratchet Crimping Tools

**CT15**

- Ratchet crimping tool for red, blue and yellow pre-insulated terminals.
- Adjustable tensioner.
- Replaceable jaws.
- Indents on jaws identify which jaw has been used.
- Ergonomically designed handles reduce operator fatigue.
- Length 230mm.
- Weight 0.6kgs.

**UCT15**

- Ratchet crimping tool for un-insulated terminals 0.5 to 6.0mm².
- Adjustable tensioner.
- Replaceable jaws.
- Ergonomically designed handles reduce operator fatigue.
- Length 225mm.
- Weight 0.51kgs.

**CT1.5-1.6**


- Ratchet crimping tool for smaller copper tube terminals.
- Suitable for volume use on terminals up to 6.0mm² and occasional use on terminals up to 16mm².
- For volume use of 10mm² and 16mm² terminals use tool no. CT10-16.
- Adjustable tensioner.
- Replaceable jaws.
- Ergonomically designed handles reduce operator fatigue.
- Length 225mm.
- Weight 0.51kgs.

**CT10-16**

- Ratchet crimping tool specifically designed for crimping 10 and 16mm² copper tube terminals.
- Ideal for IEE specification earthing bond work.
- Adjustable tensioner.
- Ergonomically designed handles reduce operator fatigue.
- Length 242mm.
- Weight 0.54kgs.

**CT6-25**

- Ratchet crimping tool for crimping 6mm² to 25mm² copper tube terminals.
- Ergonomically designed handles reduce operator fatigue.
- Length 36cm.
- Weight 0.9kg.

**CEFT1, 2 and 3**

- CEFT1 - for cord end ferrules 0.5 to 6.0mm².
- CEFT2 - for cord end ferrules 4 to 16mm².
- CEFT3 - for cord end ferrules 16 to 35mm².
- Adjustable tensioner.
- Replaceable jaws.
- Ergonomically designed handles reduce operator fatigue.
- Polished jaws mean that ferrules release easily after crimping.
- Length CEFT1 and CEFT2 205mm, CEFT3 226mm
- Weight CEFT1 and CEFT2 0.39kgs, CEFT3 0.54kgs.