

Mineral Insulated Glands RGM – 5A

Designed to be used on mineral insulated cables.

Precision manufactured from brass.

Glands are compatible with zone 1 & 2.

BASEFFA Approved.

Standard: ATEX ZONES 1 & 2 EEXD.



RPS & RPSL Seals – 5A

Pots designed for use with mineral insulated glands.

RPS - Standard.

RPSL - Earth tail seal.

ATEX Seals available on request.



RZP & RZE Sleeve – 5A

Designed for use on mineral conductors.

Maximum temperature 105°C.

Available in red or black.

Sold in 3m packs.



RHG Insulating Shrouds – 5A

Cable gland shrouds manufactured in three materials for use with RGM Glands.

Available in:-

1. PVC Grade
2. LSF Material UL94V1
3. Zero halogen silicon material.

Available in sizes, 20mm, 25mm, 32mm.



RCHL & RSFL Cable Clips + Saddles – 5B

Clips and saddles designed for mineral insulated and soft skin fire cables.

Manufactured from copper with a LSF powder coating.

Part No. P CLIP	Min/Max cable range mm
RCHL28	7 - 7.4
RCHL30	7.5 - 7.9
RCHL32	8 - 8.4
RCHL34	8.5 - 9
RCHL37	9.1 - 10
RCHL40	10.1 - 10.7
RCHL43	10.6 - 11.7

Part No. 2 WAY SADDLE	Min/Max cable range mm
RSFL302	7 - 7.7
RSFL342	7.8 - 9.0
RSFL382	9.1 - 9.7

