



Make the switch

## 6A 10kA TP Type C MCB

**Stock code:** CPB1006C3



### Technical

<b>Associated standards:</b>	BS EN 60898
<b>Ambient operating temperature:</b>	-5 to 40°C (24hour average not exceeding 25°C)
<b>Base material:</b>	
<b>Display:</b>	
<b>Earth type:</b>	
<b>Face plate material:</b>	
<b>Fault current rating (mA):</b>	
<b>Fixing screws:</b>	
<b>IP rating:</b>	
<b>Maximum installation altitude :</b>	2000m
<b>Minimum switch contact gap :</b>	4 mm
<b>Minimum wall box depth :</b>	
<b>Nature of supply:</b>	
<b>Operational testing :</b>	
<b>Output voltage:</b>	
<b>Rated current:</b>	6A
<b>Rated frequency:</b>	50-60Hz
<b>Rated kA :</b>	10
<b>Rated VA :</b>	
<b>Rated voltage:</b>	220-415V
<b>Rated watts :</b>	
<b>Switched poles :</b>	3 pole
<b>Terminal capacity :</b>	
<b>Trip characteristics:</b>	C

**Technical:** +44 (0) 208 208 7414 **Sales:** +44 (0) 208 208 7419 **E-mail:** sales@contactum.co.uk