




Aluminium Claw Cleats

Description

- Suitable for use with cables from 10 to 51mm in diameter
- Available in 9 sizes
- Can be used for all types of cable routes
- Plain finish - for indoor dry normal industrial use or outdoor unpolluted areas
- Operating temperature: -60°C to +100°C
- Two piece single fixing design
- Can be stacked to a maximum of 3 on one fixing

CABLE AND CLEAT SELECTION			CLEAT DETAILS						
Part No.	Cable Diameter A (mm)		Dimensions (mm)				Approx. Weight (g)	SWL (FOS 3) Kg	Stud Size
	Min	Max	B	C	D	E			
ACC10-13	10	13	21	38	46	16	60	150	M10
ACC13-16	13	16	36	44	43	16	50	148	M10
ACC16-19	16	19	38	48	43	18	60	121	M10
ACC19-22	19	22	38	50	43	18	70	112	M10
ACC22-25	22	25	40	53	43	20	80	95	M10
ACC25-32	25	32	44	59	43	24	90	85	M10
ACC32-38	32	38	50	65	43	27	110	83	M10
ACC38-44	38	44	56	71	43	30	120	60	M10
ACC44-51	44	51	63	78	43	33.5	150	62	M10

SWL: Safe Working Load FOS 3: Values include a safety factor of 3

Sold in eases

Method of Fixing

In all applications the cleats should be mounted on suitable fixings.

