



## Aluminium Two Bolt Cleats

### Description

- Suitable for use with cables from 51mm to 114mm in diameter
- Available in 10 sizes
- Can be used for all types of cable routes
- Plain finish - for indoor dry normal industrial use or outdoor unpolluted areas
- Operating temperature: -60°C to +100°C
- Two piece two fixing design
- Can be double stacked on common fixings

CABLE AND CLEAT SELECTION			CLEAT DETAILS						
Part No.	Cable Diameter A (mm)		Dimensions (mm)				Approx. Weight (g)	SWL (FOS 3) (Kg)	Stud Size
	Min	Max	B	C	D	E			
<b>ATC51-57</b>	51	57	68	96	49	38	230	408	M10
<b>ATC57-64</b>	57	64	75	96	49	38	240	665	M10
<b>ATC64-70</b>	64	70	84	134	64	57	410	622	M10
<b>ATC70-76</b>	70	76	90	134	64	57	400	617	M10
<b>ATC76-83</b>	76	83	96	142	64	57	410	600	M12
<b>ATC83-89</b>	83	89	102	142	64	57	490	600	M12
<b>ATC89-95</b>	89	95	114	154	76	63	650	600	M12
<b>ATC95-101</b>	95	101	120	154	76	63	650	600	M12
<b>ATC101-108</b>	101	108	134	169	76	70	900	600	M12
<b>ATC108-114</b>	108	114	140	169	76	70	900	600	M12

SWL: Safe Working Load FOS 3: Values include a safety factor of 3

Sold in eaches

### Method of Fixing

In all applications the cleats should be mounted on suitable fixings.

