

## Inline Shower Fan Range

Designed for the safe ventilation of bathrooms, toilets and shower rooms by removing any risk of an electric shock in wet areas as the fan is mounted remotely.

### Cat No.

LSF100T

### Product Type

100mm Timer model incorporating integral adjustable electronic timer (1-20 mins). Also comes with 1.5m PVC ducting, grille fixing clips, cable ties, screw plugs as well as both internal and external grilles.

LSF150T

150mm Timer model incorporating integral adjustable electronic timer (1-20 mins). Also comes with 3m PVC ducting, grille fixing clips, cable ties, screw plugs as well as both internal and external grilles.

### Additional Information

Maximum pressure:  
Fan speed :  
Sound Volume :  
Maximum operating temperature:  
Maximum Airflow l/s:  
Power Consumption (Watts):

### 4" (100mm)

20 p.a.  
2400 r.p.m.  
41.dB(A)  
40°C  
24  
10.4

### 6" (150mm)

50 p.a.  
2400 r.p.m.  
40.0 dB(A)  
40°C  
63  
20.2



**SFP Down To**  
**0.43 4" (100mm)**  
**0.31 6" (150mm)**

## Showerlite Fan Range

The Manrose Showerlite is a distinctive Showerlite which is incorporated into a circular diffuser, suitable for showers and bathrooms. The Showerlite can be used within the splash area of the shower or bath and is powered by a S.E.L.V. remote safety isolating transformer.

### Cat No.

LSLKTC

### Product Type

100mm Showerlite fan kit, complete with a adjustable over run timer (1-20mins) with chrome/white fitting showerlite and 12 volt transformer. Also comes with 1.5m PVC ducting, butterfly clips, cable ties, screw plugs as well as both internal and external grilles.

LSL-150TC

150mm Showerlite fan kit, complete with a adjustable over run timer (1-20mins) with chrome/white fitting showerlite and 12volt transformer. Also comes with 3m PVC ducting, butterfly clips, cable ties, screw plugs as well as both internal and external grilles.

### Additional Information

Maximum pressure:  
Fan speed :  
Sound Volume :  
Maximum operating temperature:  
Maximum Airflow l/s:  
Power Consumption (Watts):

### 4" (100mm)

20 p.a.  
2400 r.p.m.  
41.dB(A)  
40°C  
24  
10.4

### 6" (150mm)

50 p.a.  
2400 r.p.m.  
40.0 dB(A)  
40°C  
63  
20.2



**SFP Down To**  
**0.43 4" (100mm)**  
**0.31 6" (150mm)**

## Centrifugal Fan Range

The LM200 range of centrifugal bathroom fans are designed for ducted ventilation of internal bathrooms and WC's. The unit is able to be either surface or flush mounted due to its unique cassette design of the motor and impeller assembly. The rear spigot can be mounted in 2 positions allowing for rear exit or connecting to a vertical ducted system.

### Cat No.

LM200S

### Product Type

Standard model for remote switching

LM200P

As above supplied with pullcord switch

LM200T

Timer model incorporating integral adjustable electronic timer (1-20 mins)

LM200H

Humidity control which is adjustable between 40% RH and 95% RH complete with integral adjustable timer (1-20 mins)

LM200HP

Electronic Humidity control with pullcord over ride switch require no switched live.

### Additional Information

Maximum pressure:  
Fan speed :  
Sound Volume :  
Maximum operating temperature:  
Maximum Airflow l/s:  
Power Consumption (Watts):

79 p.a.  
2400 r.p.m.  
36.0 dB(A)  
40°C  
26  
12.4



**SFP Down To**  
**0.47**