

Cablecraft - CTT Crimping Solutions


Easy Entry Pre-Insulated Crimp Terminals



B

Easy Entry Pre-Insulated Crimp Terminals are made from oxygen-free high conductivity copper. They are electro-tin plated for excellent conductivity and resistance to corrosion. Push-On terminals are made from brass, while the insulated types benefit from an additional internal copper sleeve, ensuring insulation support and a good crimp joint.

RING TERMINALS



SPECIFICATIONS

MATERIAL:

Electro-Tin Plated Copper

INSULATION:

Polyvinyl Chloride

MAX. ELEC. RATING:

■ 19 AMP ■ 27 AMP ■ 48 AMP
600 volts - Max Temp: 75°C

APPROVALS:

UL Approved E211389
RoHS Compliant



DIMENSIONS (mm)

WIRE Ø mm ²	PART NO.	STUD SIZE D2 mm	B	L	F	E	D	D1	PACK QTY
0.5 - 1.5 RED	CIR1-2	2.2	6.6	19.6	6.3	10.0	4.1	1.7	100
	CIR1-3	3.2	5.5	16.7	4.0	10.0	4.1	1.7	100
	CIR1-3.5	3.7	5.5	16.7	4.0	10.0	4.1	1.7	100
	CIR1-4	4.3	8.0	21.0	7.0	10.0	4.1	1.7	100
	CIR1-5	5.3	8.0	21.0	7.0	10.0	4.1	1.7	100
	CIR1-6	6.5	11.6	26.8	11.1	10.0	4.1	1.7	100
	CIR1-8	8.4	11.6	26.8	11.1	10.0	4.1	1.7	100
	CIR1-10	10.5	13.6	30.7	13.9	10.0	4.1	1.7	100
	CIR1-12	13.0	19.2	35.6	16.0	10.0	4.1	1.7	100
1.5 - 2.5 BLUE	CIR2-3	3.2	6.4	17.5	4.3	10.0	4.5	2.3	100
	CIR2-3.5	3.7	6.4	17.5	4.3	10.0	4.5	2.3	100
	CIR2-4	4.3	8.5	22.0	7.8	10.0	4.5	2.3	100
	CIR2-5	5.3	9.5	22.0	7.3	10.0	4.5	2.3	100
	CIR2-6	6.5	12.0	27.0	11.0	10.0	4.5	2.3	100
	CIR2-8	8.4	12.0	27.0	11.0	10.0	4.5	2.3	100
	CIR2-10	10.5	13.6	30.7	13.9	10.0	4.5	2.3	100
	CIR2-12	13.0	19.2	35.6	16.0	10.0	4.5	2.3	50
4 - 6 YELLOW	CIR3-3.5	3.7	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-4	4.3	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-5	5.3	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-6	6.5	12.0	29.0	10.5	12.5	6.5	3.4	50
	CIR3-8	8.4	15.0	33.7	13.7	12.5	6.5	3.4	50
	CIR3-10	10.5	15.0	33.7	13.7	12.5	6.5	3.4	50
	CIR3-12	13.0	19.2	38.1	16.0	12.5	6.5	3.4	50