



Uninsulated copper brazed sheet crimp terminals

Cablecraft's range contains sizes for cables from 0.5mm² - 6mm² and stud sizes from 2.2mm to 10.5mm. They maintain strength during the crimping cycle, and are electro tin plated for maximum corrosion resistance and conductivity.

Uninsulated fork terminals


SPECIFICATIONS

Material Oxygen-free, high conductivity copper sheet with high ductility silver alloy brazing.

Approvals UL approved
E211389, RoHS 2

600 volts

Maximum temperature 75°C



Uninsulated fork terminals

Wire Ø mm ²	Max. elect. rating (A)	Part number	Stud size D2 (mm)	Dimensions (mm)						Pack qty
				B	L	F	E	D	D1	
0.5 - 1.5	19	CF1-3N	3.2	5.0	16.0	6.3	5.0	3.4	1.7	100
	19	CF1-3	3.2	5.8	16.0	6.3	5.0	3.4	1.7	100
	19	CF1-3.5	3.7	5.8	16.0	6.3	5.0	3.4	1.7	100
	19	CF1-4	4.3	6.4	15.6	6.3	5.0	3.4	1.7	100
	19	CF1-5	5.3	8.0	16.0	7.0	5.0	3.4	1.7	100
1.5 - 2.5	27	CF2-3N	3.2	5.0	16.0	6.3	5.0	4.1	2.3	100
	27	CF2-3	3.2	5.8	16.0	6.3	5.0	4.1	2.3	100
	27	CF2-3.5	3.7	6.4	16.0	6.3	5.0	4.1	2.3	100
	27	CF2-4	4.3	6.4	16.0	6.3	5.0	4.1	2.3	100
	27	CF2-5	5.3	8.5	17.0	7.3	5.0	4.1	2.3	100
4 - 6	48	CF3-3.5	3.7	7.2	18.7	7.5	6.0	5.6	3.4	50
	48	CF3-4	4.3	8.5	18.7	7.5	6.0	5.6	3.4	50
	48	CF3-5	5.3	9.5	18.7	7.5	6.0	5.6	3.4	50
	48	CF3-6	6.5	12.0	24.7	12.0	6.0	5.6	3.4	50

Uninsulated ring terminals


SPECIFICATIONS

Material Oxygen-free, high conductivity copper sheet with high ductility silver alloy brazing.

Approvals UL approved
E211389, RoHS 2

600 volts

Maximum temperature 75°C



Uninsulated ring terminals

Wire Ø mm ²	Max. elect. rating (A)	Part no.	Stud size D2 (mm)	Dimensions (mm)						Pack qty
				B	L	F	E	D	D1	
0.5 - 1.5	19	CR1-2	2.2	6.6	14.6	6.3	5.0	3.4	1.7	100
	19	CR1-3	3.2	5.5	11.7	4.0	5.0	3.4	1.7	100
	19	CR1-3.5	3.7	5.5	11.7	4.0	5.0	3.4	1.7	100
	19	CR1-3.5L	3.7	6.6	14.6	6.3	5.0	3.4	1.7	100
	19	CR1-4	4.3	6.6	14.6	6.3	5.0	3.4	1.7	100
	19	CR1-4L	4.3	8.0	16.0	7.0	5.0	3.4	1.7	100
	19	CR1-5	5.3	8.0	16.0	7.0	5.0	3.4	1.7	100
	19	CR1-6	6.5	11.6	21.8	11.1	5.0	3.4	1.7	100
1.5 - 2.5	19	CR1-8	8.4	11.6	21.8	11.1	5.0	3.4	1.7	100
	27	CR2-3	3.2	6.4	12.5	4.3	5.0	4.1	2.3	100
	27	CR2-3.5	3.7	6.4	12.5	4.3	5.0	4.1	2.3	100
	27	CR2-3.5L	3.7	6.6	14.5	6.3	5.0	4.1	2.3	100
	27	CR2-4	4.3	6.6	14.5	6.3	5.0	4.1	2.3	100
	27	CR2-5	5.3	8.5	17.0	7.8	5.0	4.1	2.3	100
	27	CR2-6	6.5	12.0	22.0	11.0	5.0	4.1	2.3	100
	27	CR2-8	8.4	12.0	22.0	11.0	5.0	4.1	2.3	100
4 - 6	27	CR2-10	10.5	13.6	25.7	13.9	5.0	4.1	2.3	100
	48	CR3-3.5	3.7	7.2	15.5	5.9	6.0	5.6	3.4	50
	48	CR3-4	4.3	7.2	15.5	5.9	6.0	5.6	3.4	50
	48	CR3-4L	4.3	9.5	19.0	8.3	6.0	5.6	3.4	50
	48	CR3-5	5.3	9.5	19.0	8.3	6.0	5.6	3.4	50
	48	CR3-6	6.5	12.0	22.5	10.5	6.0	5.6	3.4	50
	48	CR3-8	8.4	15.0	27.2	13.7	6.0	5.6	3.4	50
	48	CR3-10	10.5	15.0	27.2	13.7	6.0	5.6	3.4	50