



Our range of uninsulated cord end terminals covers cable sizes from 0.5mm² to 150mm². Designed to terminate the end of a cable, prior to fitting into screw type terminal blocks or connectors. The crimped on uninsulated cord end terminal protects the exposed wire strands from damage from the screw, this results in a stronger connection.

SPECIFICATIONS

MATERIAL:

Tin Plated Electrolytic Copper

HEAT RESISTANCE:

Up to 125°C



DIMENSIONS (mm)

PART NO.	SIZE (mm ²)	L1	D1	S	PACK QTY
CUT 0.5-6	0.50	6	1	0.15	500
CUT 0.5-10	0.50	10	1	0.15	500
CUT 0.75-6	0.75	6	1.2	0.15	500
CUT 0.75-10	0.75	10	1.2	0.15	500
CUT 1.0-6	1.00	6	1.4	0.15	500
CUT 1.0-10	1.00	10	1.4	0.15	500
CUT 1.5-7	1.50	7	1.7	0.15	500
CUT 1.5-10	1.50	10	1.7	0.15	500
CUT 2.5-7	2.50	7	2.2	0.15	500
CUT 2.5-10	2.50	10	2.2	0.15	500
CUT 4.0-9	4.00	9	2.8	0.20	500
CUT 4.0-12	4.00	12	2.8	0.20	500
CUT 6.0-15	6.00	15	3.5	0.20	100
CUT 10-15	10.00	15	4.5	0.20	100
CUT 10-18	10.00	18	4.5	0.20	100
CUT 16-15	16.00	15	5.8	0.20	100
CUT 16-18	16.00	18	5.8	0.20	100
CUT 25-15	25.00	15	7.3	0.20	100
CUT 25-18	25.00	18	7.3	0.20	100
CUT 35-18	35.00	18	8.3	0.20	100
CUT 35-25	35.00	25	8.3	0.20	100
CUT 50-25	50.00	25	10.3	0.30	50
CUT 70-25	70.00	25	12.5	0.35	50
CUT 95-30	95.00	30	14.5	0.35	50
CUT 120-34	120.00	34	16.5	0.45	10
CUT 150-38	150.00	38	18.5	0.50	10