

Neoprene sleeve expander tools

A range of four high quality ultra lightweight tools ensure speedy application. They can be used for fitting neoprene sleeves with internal diameters up to 20mm.

KY1



KY2



KY3



KY4



Grommet strips and grommets

Castellated grommet strip

This versatile grommet strip comes in natural coloured polythene, is easily cut by hand and is fitted without special tools or adhesives. It is ideal for circular, oval or irregular shaped openings of all sizes in panels. Available in 9 sizes for panel thicknesses from 0.4 to 12.9mm in 25m lengths.



SPECIFICATIONS

Material Halogen free polythene
Colour options Natural
Operating temperature -30°C to +80°C
Flammability UL94 HB

Castellated grommet strip

Part no.	Panel thickness (mm)	Width (mm)	Channel width (mm)	Height (mm)	Pack quantity (m)
CGS1	0.4 - 1.0	2.2	0.95	2.4	25
CGS2	1.0 - 1.3	3.8	1.4	4.0	25
CGS3	1.3 - 2.1	4.5	2.3	4.0	25
CGS4	2.1 - 3.3	5.6	3.3	4.0	25
CGS5	3.3 - 4.8	8.3	5.0	5.8	25
CGS6	4.8 - 6.5	9.8	6.6	6.1	25
CGS7	6.5-8.1	11.4	8.3	6.8	25
CGS8	8.1-9.7	13.2	10.1	6.8	25
CGS9	9.7-12.9	16.4	13.2	6.8	25

Smooth edge grommet strip

This flexible grommet strip is suitable for a range of panel thicknesses from 0.8mm to 4.0mm.



SPECIFICATIONS

Material Non flame retardant halogen free
Colour options Natural
Operating temperature -50°C to +50°C

Smooth edge grommet strip

Part no.	Panel thickness (mm)	Pack quantity (m)
CGSS 1	0.8 - 1.0	35
CGSS 2	1.1 - 1.5	30
CGSS 3	1.6 - 2.0	25
CGSS 4	2.1 - 3.0	20
CGSS 5	3.1 - 4.0	15

Grommet strip



SPECIFICATIONS

Material Halogen free LDPE
Colour options Natural
Operating temperature -50°C to +50°C

A flexible grommet strip in LDPE, prevents chafing on panel openings and is suitable for plate thicknesses 1.0 to 6.5mm.

Grommet strip

Part no.	Size	Thickness of plate (mm)	Min corner radius (mm)	Min aperture diameter (mm)	Pack qty (m)
0494	2	1.0 - 1.1	4	22	25
0495	3	1.5 - 2.0	5	25	25
0496	4	2.5 - 3.3	6	30	25
0497	5	4.0 - 4.9	8	36	25
0498	6	4.5 - 6.5	8.5	45	25