



## Rounded and flat braided earth leads

High grade tin plated copper braided earth leads are available in a variety of sizes to suit many different applications. Typically used in automotive, aerospace, mass transit and other industrial applications.

### SPECIFICATIONS

#### Material

High-grade tin plated copper. Brazed seam terminal construction. High flexibility braid for high vibration areas.

#### Approvals

Conforms to BS4109. UL & CSA Listed terminals. bright electro tin plating to BS 1872: 1974. RoHS 2 compliant.



### Braided earth leads

| Part number | Stud size | Current rating Amps | Braid type | Dimensions                |           | Pack quantity |
|-------------|-----------|---------------------|------------|---------------------------|-----------|---------------|
|             |           |                     |            | Nom. area mm <sup>2</sup> | Length mm |               |
| BEL493      | 6         | 45                  | Round      | 4                         | 93        | 1             |
| BEL4200     |           | 45                  | Round      | 4                         | 200       | 1             |
| BEL75100    |           | 63                  | Flat       | 7.8                       | 100       | 1             |
| BEL75250    |           | 63                  | Flat       | 7.8                       | 250       | 1             |
| BEL10150    |           | 90                  | Flat       | 10                        | 150       | 1             |
| BEL10300    |           | 90                  | Flat       | 10                        | 300       | 1             |
| BEL16150    |           | 120                 | Round      | 16                        | 150       | 1             |
| BEL16300    |           | 120                 | Round      | 16                        | 300       | 1             |
| BEL25200    | 10        | 150                 | Flat       | 25                        | 200       | 1             |
| BEL25400    |           | 150                 | Flat       | 25                        | 400       | 1             |
| BEL35200    |           | 200                 | Flat       | 35                        | 200       | 1             |
| BEL35400    |           | 200                 | Flat       | 35                        | 400       | 1             |
| BEL50200    |           | 250                 | Flat       | 50                        | 200       | 1             |
| BEL50400    |           | 250                 | Flat       | 50                        | 400       | 1             |

Custom braided leads can be manufactured to your specification, see page 344.



## Flat braided earth leads - Reels

High grade tin plated braided earth lead on a reel is available in a variety of sizes to suit many different applications. Typically used in automotive, aerospace, mass transit and other industrial applications.

### SPECIFICATIONS

#### Material

High grade tin plated copper. High flexibility braid for high vibration areas.

#### Approvals

Conforms to BS4109. UL & CSA Listed Terminals. bright electro tin plating to BS 1872: 1974. RoHS 2 compliant.



### Flat braided earth lead Reels

| Part number | Current rating Amps | Reel length (m) | Dimensions                |                   | Pack quantity |
|-------------|---------------------|-----------------|---------------------------|-------------------|---------------|
|             |                     |                 | Nom. area mm <sup>2</sup> | Width x height mm |               |
| FCB10       | 10                  | 25              | 0.5                       | 2 x 0.6           | 1             |
| FCB30       | 30                  | 25              | 1.7                       | 5 x 0.7           | 1             |
| FCB63       | 63                  | 25              | 7.8                       | 10 x 2            | 1             |
| FCB90       | 90                  | 25              | 10                        | 12 x 2.3          | 1             |
| FCB120      | 120                 | 25              | 16                        | 19 x 2.3          | 1             |
| FCB150      | 150                 | 25              | 25                        | 25 x 3            | 1             |
| FCB200      | 200                 | 25              | 35                        | 25 x 3.5          | 1             |