


Our brass dome top glands offer high quality and total reliability. Suitable for use in plant and automation technologies where exceptional and safe functioning are required. Suitable for high demands, offering excellent strain relief.

SPECIFICATIONS

MATERIAL: Brass Nickel Plated
PROTECTION CLASS: IP 68
TEMPERATURE RANGE: -40°C to +100°C
CLAMPING INSERT: Polyamide 6
SEALING RING: Neoprene



METRIC GLANDS					
PART NO.	THREAD SIZE	TD (HOLE SIZE mm)	TL (LENGTH OF THREAD mm)	FOR CABLE RANGE MIN-MAX Ø (mm)	PACK QTY
EPN 700/M12	M 12 x 1.5	12.0	6.0	3.0 - 6.5	1
EPN 700/M16	M 16 x 1.5	16.0	7.0	4.0 - 8.0	1
EPN 700/M20	M 20 x 1.5	20.0	8.0	6.0 - 12.0	1
EPN 700/M25	M 25 x 1.5	25.0	8.0	10.0 - 14.0	1
EPN 700/M32	M 32 x 1.5	32.0	9.0	13.0 - 18.0	1
EPN 700/M40	M 40 x 1.5	40.0	9.0	18.0 - 25.0	1
EPN 700/M50	M 50 x 1.5	50.0	9.0	22.0 - 32.0	1
EPN 700/M63	M 63 x 1.5	63.0	14.0	34.0 - 44.0	1

METRIC LOCKNUTS				
	PART NO.	THREAD SIZE	DEPTH (mm)	PACK QTY
	EPN 710/M12	M 12 x 1.5	2.8	1
	EPN 710/M16	M 16 x 1.5	3.0	1
	EPN 710/M20	M 20 x 1.5	3.5	1
	EPN 710/M25	M 25 x 1.5	4.0	1
	EPN 710/M32	M 32 x 1.5	5.0	1
	EPN 710/M40	M 40 x 1.5	5.0	1
	EPN 710/M50	M 50 x 1.5	5.0	1
	EPN 710/M63	M 63 x 1.5	5.0	1