

**W-Series, Accessories**  
**WQV 2.5/6**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



The versatile and extensive range of products - from 0.05 mm<sup>2</sup> to 300 mm<sup>2</sup> - means that you have diverse options for your applications at your disposal.  
Hardened steel for mechanical strength and high-quality tinned copper for optimum conductivity. All materials comply with RoHS requirements and have been tested to current environment guidelines.

**General ordering data**

|            |                                                                            |
|------------|----------------------------------------------------------------------------|
| Type       | WQV 2.5/6                                                                  |
| Order No.  | <a href="#">1054060000</a>                                                 |
| Version    | W-Series, Accessories, Cross-connector, For the terminals, No. of poles: 6 |
| GTIN (EAN) | 4008190102272                                                              |
| Qty.       | 10 pc(s).                                                                  |

**W-Series, Accessories**  
**WQV 2.5/6**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|        |         |            |       |
|--------|---------|------------|-------|
| Length | 29.5 mm | Width      | 7 mm  |
| Height | 18 mm   | Net weight | 4.5 g |

**Temperatures**

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Operating temperature            |        | Storage temperature              |        |
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |

**Additional technical data**

|                          |                   |                     |                 |
|--------------------------|-------------------|---------------------|-----------------|
| Explosion-tested version | No                | Installation advice | Direct mounting |
| Version                  | For the terminals |                     |                 |

**Rated data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | Yellow |
| UL 94 flammability rating | V-2   |        |        |

**System specifications**

|                |                       |
|----------------|-----------------------|
| Product family | W-Series, Accessories |
|----------------|-----------------------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | UNSPSC     | 30-21-18-01 |
| eClass 5.1 | 27-14-11-40 | eClass 6.2 | 27-14-11-40 |
| eClass 7.1 | 27-14-11-40 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|