

# EMERGENCY

## EBLANA EMERGENCY LED BULKHEAD

NEW!



### EBLANA EMERGENCY LED BULKHEAD, MAINTAINED

- LED replacement for T5 emergency bulkheads
- Fully polycarbonate construction
- Hinged gear tray allowing for ease of wiring and installation
- R8MLEDT5-01 complete with test switch on the side of the fitting
- Only 3W in maintained mode
- No UV or IR content
- 3 hour emergency operation
- Double sided exit accessory available allowing removal of existing diffuser and conversion to double sided exit (R8MLEDDE)
- Emergency spacing details for R8MLED in back section of catalogue

#### ACCESSORIES

R8MLEDDE	BULKHEAD accessory for R8MLED
RBULKLEG	BULKHEAD legend kit
R8MLEDRSB-01	Recessed box for R8MLED
R8MLEDDEXLR	Left/right running man legend stickers for R8MLEDDE
R8MLEDDEXU	2 Up Arrow Legend Set With Running for R8MLEDDE

#### DIMENSIONS (mm)

	Length	Width	Depth
R8MLED-01	352	110	67
R8MLEDT5-01	352	110	67
R8MLEDDE	350	200	185
RBULKLEG	265	219	N/A
R8MLEDRSB-01	161	391	35
R8MLEDLST-01	352	110	67



RBULKLEG legend kit



R8MLEDRSB-01 recessed box

# EMERGENCY

## EBLANA EMERGENCY LED BULKHEAD



R8MLED with  
R8MLEDE bulkhead

	Standard	Test Switch	Self Test
	<b>R8MLED-01</b>	<b>R8MLEDTS-01</b>	<b>R8MLEDLST-01</b>
<b>Total Power (W):</b>	3.7	3.7	3.5
<b>Total Light Output (lm):</b>	140 standard 120 emergency	140 standard 120 emergency	150 standard 100 emergency
<b>Lux at 1m (lux):</b>	45 standard 40 emergency	45 standard 40 emergency	45 standard 40 emergency
<b>CCT (K):</b>	6500	6500	6000
<b>CRI (Ra):</b>	80	>65	80
<b>Power Factor (PF):</b>	0.55	0.55	0.5
<b>Impacting Rating (IK):</b>	07	07	08
<b>Weight (kg):</b>	0.57	0.57	0.57
<b>Box Qty:</b>	1	1	1

