

MAGPRO-SD1

Addressable Smoke Detector

- Sensitivity level selectable from the control panel High/Normal/Middle/Low
- Protected area - 120m²
- Installation height - up to 16m
- Day/Night mode
- Low profile design
- LED indication with 360° visibility
- Certified to EN54-7
- Base ordered separately see MAGPRO-DB, MAGPRO-DBS and MAGPRO-DBSS

**MAGPRO-HD1**

Addressable Heat Detector

- Can work as a fixed temperature or rate of rise detector
- Class A1R, A2S, BS selectable from the control panel
- Day/Night mode
- Protected area - up to 35m²
- Installation height - up to 3.5m
- Low profile design
- LED indication with 360° visibility
- Certified to EN54-5
- Base ordered separately see MAGPRO-DB, MAGPRO-DBS and MAGPRO-DBSS

**MAGPRO-HSD1**

Combined Smoke & Heat Detector

- Sensitivity selectable from the control panel -High/Normal/Middle/Low
- Class A1R temperature sensor (according to EN54-5)
- Protected area - up to 120m²
- Installation height - up to 16m
- Day/Night mode
- Low profile design
- LED indication with 360° visibility
- Certified to EN54-5/7
- Base ordered separately see MAGPRO-DB, MAGPRO-DBS and MAGPRO-DBSS

**MAGPRO-DB**
Detector Base**MAGPRO-DBS**
Sounder Base**MAGPRO-DBSS**
Sounder Strobe Base**MAGPRO-DBSC**
Detector Base Cover Blank Plate