

Downlight Spares

Applies to Firehood only :-

The KingShield Firehood has a 60 minute fire rating. It is suitable to cover a wide range of mains & low voltage downlights. It is also ventilated to reduce heat build up.

- Prevents fire from penetrating the ceiling void and retains ceiling's fire protection integrity

Technical Data

Conforms to BS476 Part 23.

	Part No	Description	Colour
	DLR	Lamp Retainer Ring	Chrome
	LVHDL	Spare lampholder for low voltage downlights	-
	GUHDL	Spare lampholder for GU downlights	-
	FH1	60 Minute Firehood Conforms to BS 476 part 23 ø150 x 150mm	White

Transformers

These transformers are built to be maintenance free in an extremely compact design allowing easy installation through the luminaire aperture. Complete with built in auto-resetting short circuit protection and thermal overload fuse cut out.

Technical Data

ETR60 auto-resetting thermal overload

EMC approved

Conforms to EN 61347-2-2

	Part No	Description	Dimensions
	ETR60	60VA Dimmable Transformer Supplied with leads Auto reset overload, short circuit and thermal protection 5 year guarantee	H30 x W120 x D20mm
	LT105T	105VA Electronic Transformer Dimmable 35W - 105W	H48 x W150 x D37mm
	LT150T	150VA Electronic Transformer Non-Dimmable	H58 x W215 x D48mm