


**Product Description:****OrbitalCWS™ 10-20W Colour & Wattage Switchable IP66 Bulkhead**


Three colour temperatures and three wattages in one product! Being IP66 rated makes this new OrbitalCWS™ ideal for outdoor and damp locations. Additionally, this product offers plug and play emergency and microwave sensor packs making the range perfect for the wholesaler to control stock levels and store less products, whilst also being simple for the contractor to convert on site. 54 product combinations in one!

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-BH21CWSBLK	10	3000K	950	120	Black	Non Dimmable
AU-BH21CWSBLK	10	4000K	1000	120	Black	Non Dimmable
AU-BH21CWSBLK	10	6500K	950	120	Black	Non Dimmable
AU-BH21CWSBLK	14	3000K	1350	120	Black	Non Dimmable
AU-BH21CWSBLK	14	4000K	1400	120	Black	Non Dimmable
AU-BH21CWSBLK	14	6500K	1350	120	Black	Non Dimmable
AU-BH21CWSBLK	20	3000K	1900	120	Black	Non Dimmable
AU-BH21CWSBLK	20	4000K	1900	120	Black	Non Dimmable
AU-BH21CWSBLK	20	6500K	1900	120	Black	Non Dimmable
AU-BH21CWSW	10	3000K	1050	120	White	Non Dimmable
AU-BH21CWSW	10	4000K	1100	120	White	Non Dimmable
AU-BH21CWSW	10	6500K	1050	120	White	Non Dimmable
AU-BH21CWSW	14	3000K	1450	120	White	Non Dimmable
AU-BH21CWSW	14	4000K	1500	120	White	Non Dimmable
AU-BH21CWSW	14	6500K	1450	120	White	Non Dimmable
AU-BH21CWSW	20	3000K	2000	120	White	Non Dimmable
AU-BH21CWSW	20	4000K	2000	120	White	Non Dimmable
AU-BH21CWSW	20	6500K	2000	120	White	Non Dimmable


Line Drawing



Polar Curve



Colour



Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Wattage switchable between 10W, 14W and 20W
- IP66 rated
- IK10 rated
- Four side and rear conduit entries
- -20 to +45 ambient operating temperature
- Plug and play emergency, emergency self-test and microwave sensing packs available
- 5 Year Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.8
Lifetime L70 (hrs)	50000hrs
Lamp Base	None
Weight (Kg)	0.872
Product Type	Bulkheads
Operating Temp. (Max) °C	45°C

Input Frequency	50/60HZ
IP Rating	IP66
IK Rating	IK10
Overall Diameter (mm)	300
Projection (mm)	95
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.