

Technical Specification



Product Code: MD046RDTT Description: 13A/10AX Double Pole Keyswitch Module





General Information

 $\label{eq:decomposition} \textbf{Dimensions} \qquad 25 \text{mm (W)} \ \text{x} \ 52.5 \text{mm (H)} \ \text{x} \ 20 \text{mm (D)}$

Aperture Dimensions 16mm (W) x 31.5mm (H)

Finish Red

Materials Cover & Rocker Switch: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz

Load Rating 10AX (Suitable For Inductive Loads)

Terminal Size 3.5mmø **Terminal Torque** 0.4Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²

Product Markings Test

Back Box Depth Dependent On Plate Used

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.