

**GLS BULB WITH DUSK TO DAWN DUAL SENSOR B22 470LM 4.8W 2700K
NON-DIMM 240 BEAM FROSTED INTEGRAL**

ILGLSB22SC125



This 4.8W retro-fit Integral LED Auto Sensor Classic Globe (GLS) (large bayonet base) delivers a warm light equivalent to 40W. Because security lighting is on an average of 12 hrs. per day you can save over 20 GBP/29 EUR per bulb, per year on energy. It automatically switches ON at dusk and OFF at dawn, with dual 360 sensors to detect daylight from all angles. Ideal for external porches, walkways, paths and patios. To be used in suitable enclosed outdoor fittings.

Details

Quick Order Code:	821745
Barcode:	5055788262442
Category:	Lamps
Range Name:	Everyday
Product Body Finish:	White
Market Segment:	Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Features:	Dusk-to-Dawn Sensor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	113
Product Width (mm):	60
Product Weight (g):	40
Material:	Aluminium, Polycarbonate, Glass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Die cast heat-sink, Glass Diffuser
Globe Finish:	Frosted
Globe Type:	GLS
Bulb or Luminaire Shape:	Round
Placement / Application:	Outdoor (with appropriate outdoor fitting), General Lighting
Spot Type:	SMD

Electrical Data



Power Consumption (W) :	4.8
Power Factor:	0.4
Wattage equivalent (W):	40
Amperage (mA):	40
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
True Wattage Eq (W):	40
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	470
Luminous efficacy (lm/W):	98
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	240
Colour Rendering Index (CRI):	80
Colour Type:	Single
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):	144
Package Length (mm):	123
Package Width (mm):	64
Package Depth (mm):	64

[Portal.integral-led.com](https://portal.integral-led.com)