



## FL02

20W colour switchable floodlight

### Features

|                 |                   |
|-----------------|-------------------|
| IK rating       | IK07              |
| IP rating       | IP65              |
| CSP Switchable  | Colour switchable |
| Tiltable        | 180°              |
| Rotation Angle  | 360°              |
| UGR             | UGR 14            |
| Sensor Option   | No                |
| Dimmable Option | No                |
| LED Lifetime    | 50,000h L70       |
| CRI             | 80 Ra             |
| SDCM            | 5 SDCM            |

### Installation information

|                             |                              |
|-----------------------------|------------------------------|
| Install Connector Type      | Flying lead                  |
| Inrush Current              | 11A 4745                     |
| Construction Material       | Black painted cast aluminium |
| Weight                      | 580g                         |
| Maximum Ambient Temperature | -40°C to 40°C                |
| Electric Class (1, 2, 3)    | 1                            |

### Wiring information

|                         |                                           |
|-------------------------|-------------------------------------------|
| Cable / Flying Lead     | 1m H05RN-F rubberised cable 3x1.0mm² Ø7mm |
| Type of Wiring Required | Parallel                                  |

### Accessories

|     |                         |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

### Guarantee

5 years for standard & 3 years for PIR

### Features & benefits

High efficacy of up to 120lm/W

First fix bracket for quick & easy installation

Ideal for coastal areas

Colour switchable between 3 colour temperatures

IP65 rated, meaning it provides optimum protection against the impacts of rainwater and general adverse weather conditions

A unique 360° rotation for total flexibility, and a 180° tilt

Supplied with 1m cable



Wide 120° beam angle, reducing the number of fittings per area required

Performs in even more extreme conditions from -40°C to +40°C

Light source energy efficiency:



Beam angles: C0/C180 C90/C270



Photometrics @ 25°C

|          | Finish                  | Feature I      | W   | Colour | Beam | lm   | lm/W | lx @ 1m |
|----------|-------------------------|----------------|-----|--------|------|------|------|---------|
| FL02BXCS | Black                   | Non PIR sensor | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02BXCS | Black                   | Non PIR sensor | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02BXCS | Black                   | Non PIR sensor | 20W | 6500K  | 120° | 2400 | 120  | 999     |
| FL02BPCS | Black                   | PIR sensor     | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02BPCS | Black                   | PIR sensor     | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02BPCS | Black                   | PIR sensor     | 20W | 6500K  | 120° | 2400 | 120  | 999     |
| FL02WXCS | White RAL9016           | Non PIR sensor | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02WXCS | White RAL9016           | Non PIR sensor | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02WXCS | White RAL9016           | Non PIR sensor | 20W | 6500K  | 120° | 2400 | 120  | 999     |
| FL02WPCS | White RAL9016           | PIR sensor     | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02WPCS | White RAL9016           | PIR sensor     | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02WPCS | White RAL9016           | PIR sensor     | 20W | 6500K  | 120° | 2400 | 120  | 999     |
| FL02AXCS | Anthracite grey RAL7016 | Non PIR sensor | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02AXCS | Anthracite grey RAL7016 | Non PIR sensor | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02AXCS | Anthracite grey RAL7016 | Non PIR sensor | 20W | 6500K  | 120° | 2400 | 120  | 999     |
| FL02APCS | Anthracite grey RAL7016 | PIR sensor     | 20W | 3000K  | 120° | 2200 | 110  | 832     |
| FL02APCS | Anthracite grey RAL7016 | PIR sensor     | 20W | 4000K  | 120° | 2400 | 120  | 1040    |
| FL02APCS | Anthracite grey RAL7016 | PIR sensor     | 20W | 6500K  | 120° | 2400 | 120  | 999     |



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

FL02

With a wide 120° beam angle and a unique 360° rotation, this 20W flicker-free floodlight is the ideal solution for outdoor use, lighting large areas, courtyards and entrances or for uplighting trees and buildings. With a market leading efficacy and contemporary black cast aluminium body, this colour switchable light is a versatile solution for your space.  
<br/>Choose the PIR sensor option for added security and reduction of energy bills in highly trafficked areas.