

Product datasheet

Specifications



MGF fusegear switch disconnecter 400A TP&N, AC-23B, M12, 415 V, 50/60 Hz

Local distributor code: 387294607 MGFD4003C

EAN Code : 5018934934501

Main

Range	MGF fusegear
Product or component type	Enclosed switch-disconnector
[Ue] rated operational voltage	415 V
[Ie] rated operational current	400 A

Complementary

Mechanical interlocking	Door interlocking function
Poles description	3P + N
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23B
[Uimp] rated impulse withstand voltage	8 kV
[Icw] rated short-time withstand current	12 kA
[Icm] rated short-circuit making capacity	24 kA
Maximum power	220 kW
Connections - terminals	Terminal stud 400 mm² M12 50 mm
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Enclosure material	Steel epoxy-polyester powder cream RAL 9001
Provided equipment	Removable gland plates Earthing kit

Environment

Standards	BS EN 60947-3
-----------	---------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)