

Main

Range of product	MGF fusegear
Product or component type	Enclosed switch disconnecter
Poles description	3P + N
[Ue] rated operational voltage	415 V
[Ie] rated operational current	100 A

Complementary

Mechanical interlocking	Door interlocking function
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-21A AC-22A AC-23B AC-20A
[Uimp] rated impulse withstand voltage	6 kV
[Icw] rated short-time withstand current	1300 kA
[Icm] rated short-circuit making capacity	3.5 kA
Maximum power	55 kW
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Cable cross section	50 mm ²
Enclosure material	Steel epoxy-polyester powder cream
IP degree of protection	IP41
Standards	BS EN 60947-3
Contact position indicator	Yes
Provided equipment	Earthing kit Removable gland plate with cable knockouts

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.