



Emergency Rotary Isolators

- Insulating material for wall-mounting standard applications.
- Ensures the powering down (entire or partial) of the system, isolating it safely from any electrical power supply.
- AC3-AC23A category and is also suitable for highly inductive loads.
- Complete with terminal cover and padlockable handle in “0” position.
- Rated current options from 16A up to 100A.
- IP65 protection rating as per IEC/EN 60529.
- IK08 impact resistance as per IEC/EN 62262.
- Thermoplastic material.



208164

CAM-SZ ISOLATOR SWITCH FOR EMERGENCY WITH RED HANDLE AND YELLOW COVER, IN INSULATING MATERIAL, FOR WALL MOUNTING - IP65 4X16A

TECHNICAL DATA		REGISTRY	
Poles	4P	Net weight	0.60KG
Rated current	16A	Min order quantity	1
Rated operating voltage	690V~	EAN Code	8014950014927
Frequency	50/60Hz	Gross Weight	0.69KG
Insulation Class	II	Dimensions	158X121X126 mm
IP Protection degree	IP65		
Shock resistance	IK08 according to IEC/EN 62262		
Operating category	AC-23A / AC-3		
Execution	Wall mounting		
		REFERENCE STANDARDS	STANDARDS
		EN 60947-3:2009/A1:2012	2011/65/EU (RoHS)
		EN 60947-1:2007/A1:2011	2012/19/EU (WEEE)
		EN 60947-3:2009/A2:2015	2014/35/EU (LVD)
		EN 60947-1:2007	
		EN 60947-3:2009	
		EN IEC 63000:2018	
		EN 60947-1:2007/A2:2014	