

PRODUCT DATASHEET

L 70 W/840

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	70 W
Construction wattage	70.00 W
Nominal voltage	126 V
Nominal current	685 mA

Photometrical data

Luminous flux	6200 lm
Luminous efficacy	89 lm/W
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.95
Rated LLMF at 6,000 h	0.94
Rated LLMF at 8,000 h	0.92
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89



Dimensions & Weight

Overall length	1778.00 mm
Length with base excl. base pins/connection	1764 mm
Diameter	28.00 mm
Tube diameter	26 mm

Product weight	214.00 g
----------------	----------

Lifespan

Lifespan	20000 h
Service life	18000 h ¹⁾
Rated lamp survival factor at 2,000 h	1.00
Rated lamp survival factor at 4,000 h	1.00
Rated lamp survival factor at 6,000 h	1.00
Rated lamp survival factor at 8,000 h	1.00
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	3.1 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	70.00 kWh/1000h

Country-specific categorizations

ILCOS	FD-70/840-E-G13-26/1800
Order reference	L 70W/840

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No

Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	1778.00 mm
Height	28.00 mm
Width	28.00 mm
Chromaticity coordinate x	0,380
Chromaticity coordinate y	0,380
Beam angle correspondence	SPHERE_360
EPREL ID	546375
Model number	AC34122

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

Documents and certificates	
	Declarations Of Conformity CE
Photometric and lighting design files	
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321003959	Sleeve 1	28 mm x 28 mm x 1,795 mm	302.80 g	1.41 dm ³
4008321003966	Shipping box 25	1,820 mm x 148 mm x 145 mm	8059.00 g	39.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.