Revision Date 05/06/2018

Revision 17

Supersedes date 10/11/2017

SAFETY DATA SHEET DEFIANCE LUBE MAINTENANCE SPRAY 400ML 1030005710

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name DEFIANCE LUBE MAINTENANCE SPRAY 400ML 1030005710

Product No. ESKILUBE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited

Salmon Fields,

Royton,

Oldham, Lancashire

OL2 6HZ, England 0161 627 0101

sds@jamesbriggs.co.uk

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Aerosol 1 - H222
Human health EuH066;STOT SE 3 - H336
Environment Aquatic Chronic 3 - H412

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008





Signal Word Danger

Hazard Statements

H222 Extremely flammable aerosol.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing vapour/spray.

P501 Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50

°C/122°F.

Supplemental label information

EUH066 H229 Repeated exposure may cause skin dryness or cracking.

Pressurised container: May burst if heated

2.3. Other hazards

None noted

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

BUTANE		10-30%
CAS-No.: 106-97-8	EC No.: 203-448-7	Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification (67/548/EEC) F+;R12
ISOBUTANE		5-10%
CAS-No.: 75-28-5	EC No.: 200-857-2	Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification (67/548/EEC) F+;R12
MINERAL OIL (REFINED)		10-30%
CAS-No.: 64742-52-5	EC No.: 265-155-0	Registration Number: 01-2119467170-45-XXXX
Classification (EC 1272/2008) Not classified.		Classification (67/548/EEC) Not classified.
NAPHTHA (PETROLEUM), HYDRO	TREATED HEAVY	30-60%
CAS-No.: 64742-48-9	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304		Classification (67/548/EEC) Xn;R65. R10,R66,R67.
n-OLEOYL SARCOSINE		< 1%
CAS-No.: 110-25-8	EC No.: 203-749-3	Registration Number: 01-2119488991-20-XXXX
Classification (EC 1272/2008) Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Acute 1 - H400		Classification (67/548/EEC) Xn;R20. Xi;R38,R41. N;R50.

OLEYL HYDROXYETHYL IMIDAZOLINE < 1%

CAS-No.: 95-38-5 EC No.: 202-414-9 Registration Number: 01-2119777867-13-XXXX

Classification (EC 1272/2008) Classification (67/548/EEC)

Acute Tox. 4 - H302 Xn;R48/22,R22. Skin Corr. 1B - H314 C;R34. STOT RE 2 - H373 N;R50/53.

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

XYLENE < 1%

CAS-No.: 1330-20-7 EC No.: 215-535-7 Registration Number: 01-2119488216-32-XXXX

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 R10

Acute Tox. 4 - H312 Xn;R20/21

Acute Tox. 4 - H332 Xi;R38

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eve contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

NOTE! Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable

6.2. Environmental precautions

Not applicable

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Not applicable

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
MINERAL OIL (REFINED)			5 mg/m3		10 mg/m3	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY			1000 mg/m3			
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Straw.

Odour Characteristic.

Solubility Insoluble in water

Flammability Limit - Lower(%) 0.6 Flammability Limit - Upper(%) 9.0

9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not known.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials To Avoid See section 10.4

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Data set not currently available.

12.2. Persistence and degradability

Not applicable

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

Not determined

12.5. Results of PBT and vPvB assessment

Not applicable

12.6. Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS (WHITE SPIRIT)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group N/A
IMDG Packing group N/A
ICAO Packing group N/A

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

EMS F-D, S-U

Tunnel Restriction Code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Aerosol Dispensers (Amendment) Regulations 2014 No.1130

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

EU Legislation

The Aerosol Dispensers Directive 1975/324 EEC

Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations

Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH)

2001/95/EC The General Product Safety Directive (GPSD)

Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date 05/06/2018

Revision 17

Supersedes date 10/11/2017

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking., H220 Extremely flammable gas., H222 Extremely flammable aerosol., H226 Flammable liquid and vapour., H302 Harmful if swallowed., H304 May be fatal if swallowed and enters airways., H312 Harmful in contact with skin., H314 Causes severe skin burns and eye damage., H315 Causes skin irritation., H318 Causes serious eye damage., H319 Causes serious eye irritation., H332 Harmful if inhaled., H335 May cause respiratory irritation., H336 May cause drowsiness or dizziness., H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure., H400 Very toxic to aquatic life., H410 Very toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.