



Steel Test Plugs (Type 920) with Pneumatic Seals



- Multiple compression points around the perimeter of the plug enable the seal to expand in localised areas.
- Strength where it matters – at the compression point.
- Steel components are painted against corrosion.
- The Plugs are fitted with handle bars, to make it easier to locate the plug in the pipe.
- Can be supplied with twin outlets – lower outlet allows complete emptying of water from the drain before removal of the plug.
- Chemical resistant Seals can be supplied to order.
- “Double Seal” plugs supplied as standard.

Contact our Sales Department on :-

Telephone : 00 44 1902 60 40 60
Fax No : 00 44 1902 60 33 66
Email : sales@horobin.co.uk
Web Site : www.horobin.co.uk
Address : Horobin Limited, Midacre, Willenhall Trading Estate, Willenhall
WV13 2JW, UK



Multi-lock Steel Test Plugs 450mm to 3000mm



- Multiple compression points around the perimeter of the plug enable the seal to expand in localised areas.
- Strength where it matters – at the compression point.
- Steel components are aluminium coated against corrosion.
- The Plugs are fitted with handle bars, to make it easier to locate the plug in the pipe.
- Can be supplied with twin outlets – lower outlet allows complete emptying of water from the drain before removal of the plug.
- Chemical resistant Seals can be supplied to order.
- “Double Seal” plugs can be supplied to order.
- “Instructions for use” label on each plug.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are available on our Web Site.

Contact our Sales Department on :-

Telephone : 00 44 1902 60 40 60
Fax No : 00 44 1902 60 33 66
Email : sales@horobin.co.uk
Web Site : www.horobin.co.uk
Address : Horobin Limited, Midacre, Willenhall Trading Estate, Willenhall
WV13 2JW, UK