

Technical Data Sheet	Title: 0916	
Effective Date: Jan 2020	Prepared By: Sam Murphy	
Issue Number: 12	Authorised By: Robin Lamb	

Product Description

Clear LDPE virgin material with 30% recycled content carpet protection film coated with water based acrylic adhesive, supplied individually boxed or bulk

Applications

Temporary protection for carpets, mosquettos and sensitive surfaces against dirt & damage.

Features & Benefits

Protects against decorating spills & dirt during building works, remodelling.

Heavy duty rip resistant material.

High foot traffic when moving house & parties

Suitable for use on stair,

Fast installation & removal.

Self-adhesive for secure positioning

Technical Performance

Description	Units	Value
Substrate		LDPE
Total Thickness	mm	0.05mm ± 10%
Colour		Transparent
Density	g/cm ³	0.925
Tensile Strength (MD)	N/25mm	>15
Tensile strength (CD)	N/25mm	>10
Adhesion to stainless steel	g/25mm	500g/25mm ± 10%
Static shear 23°C	hours	>48
Elongation at break (MD)	%	>200
Elongation at break (CD)	%	>350

Declaration of Conformity Information

Not Applicable

REACH SVHC Status

NO SVHC present according to candidates list of the **UK 25/06/20 & EU 14/06/23**

RoHS Compliance Status

Not Applicable

Storage Details

Tape can be stored for 6 months in dry conditions in its original packaging.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)

Technical Data Sheet	Title: 0916	 BRUCE DOUGLAS MARKETING
Effective Date: Jan 2020	Prepared By: Sam Murphy	
Issue Number: 12	Authorised By: Robin Lamb	

Application Guidelines

Applications Notes

1. Before applying the film ensure the surface is clean & dry.
2. Customers must fully evaluate the product by testing prior to using. Test the film for 48 hours on a small hidden area of carpet to ensure compatibility with the particular carpet and to ensure there is no adhesive transfer on the carpet.
3. To apply the roll, lay it on the floor facing the direction required to cover. Push the roll forward a small distance and press down firmly to ensure the film has adhered to the carpet.
4. Continue to unroll, pressing down and smoothing out any air pockets, checking the film is rolled straight.

Limitations

1. Do not leave the film on carpet for longer than 30days.
2. For use on Synthetic Carpets Only.
3. Film is one time use only. Remove and dispose of in accordance with local environmental regulations.
4. Do not use on wool or oriental carpets. Not suitable for use on rugs, worn carpets, or loose fitted carpet tiles.
5. Do not use on hard surfaces, such as hardwood, ceramic tile, linoleum, vinyl flooring or marble.
6. Do not apply on newly laid carpets where a glue or adhesive has been used. Allow up to 72 hours for any vapours to evaporate before laying the film.
7. Do not apply to a damp surface which will prevent any moisture from evaporating and could cause discoloration of carpet fibres.
8. If carpet has been recently cleaned, allow it to completely dry for a minimum of 10 days before using the film.
9. High traffic areas or outdoor exposure may require renewal of film weekly.
10. The product should be stored no longer than 6months at room temperature.
11. Check for adhesive transfer on a regular basis.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)