

Technical Data Sheet	Title: 092012SEAL-STD	
Effective Date: Oct 2019	Prepared By: Sam Murphy	
Issue Number: 5	Authorised By:	

Product Description

Manually operated sealer for use with 12mm polypropylene strapping and metal seals.



Applications

For regular duty occasional usage, this tool is typically used in general industries for strapping parcels and pallets. Used in conjunction with 0920TSTD

For use with seal type

Recommend to be used with polypropylene strapping up to 0.55 - 0.75mm thickness

Declaration of Conformity Information

REACH SVHC Status – NO SHVC present according to candidates list of the **UK 25/06/20 & EU 08/07/21**

RoHS Compliance Status – Not Applicable

Storage Details

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)