

Stretch Film

Stretch wrap is the most cost effective way to palletise your products. We stock a comprehensive range including flushcore (STD) and extended core hand film, black opaque security film, handy wrap mini bundling reels and jumbo machine applied rolls.

Extended core blown and cast films allow smooth, low friction application with standard palletising.

Machine applied stretch films are strong, versatile and available for use with either standard core brake machines or power pre stretch machines. (see page 20 for our stretch machines)

Blown Stretch Film:

- Excellent Puncture Resistance
- High Tackability
- Superior Load Stabilisation
- Temperature Resistant

Cast Stretch Film:

- High Clarity
- Smooth Finish
- Strength & Cling without additives
- High Performance Film

Black opaque film for palletising secure and confidential consignments to guarantee pallet contents cannot be identified.
Other colours available

Handy Wrap Mini Reels are ideal for securing small boxes or bundling awkward items together for use with handy ergonomic dispenser. **CLEAR OR BLACK**

Flush core blown and cast films for standard palletising and deep freeze storage. Can be used with our range of dispensers.

Coloured stretch

Stretch film dispenser

RECYCLE

Q-Lite Pre-Stretch Film

Q-Lite pre-stretch film makes wrapping pallets easier and more efficient. There is no need to stretch the film thus giving less operator fatigue and back strain. Q-Lite allows for superior load holding, lower packaging cost, reduced waste and high tear and impact resistance.

Applying Q-Lite is quick, easy and safe:

1. Q-Lite is already pre-stretched so needs less tension and is easier to apply. Unwind one metre of film and tie to the foot of the pallet.
2. Wrap around the base of the load and the pallet 3-4 times to secure the two together.
3. Continue to wrap around the load in an upward spiral motion allowing a 30-50% overlap.
4. At each corner, stretch the film slightly and continue to wrap without using force.
5. To finish, tear off the roll and secure the loose end to the pallet by applying light pressure with the palm of your hand.

